


Kingtronics®

MMBT8550

PNP Silicon Epitaxial Planar Transistors

For switching and amplifier applications

As complementary types the NPN transistors MMBT8050 is recommended.



1.Base 2.Emitter 3.Collector
SOT-23 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

PARAMETER	SYMBOL	VALUE	UNIT
Collector Base Voltage	$-V_{CBO}$	40	V
Collector Emitter Voltage	$-V_{CEO}$	25	V
Emitter Base Voltage	$-V_{EBO}$	6	V
Collector Current	$-I_C$	600	mA
Power Dissipation	P_{tot}	350	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_s	- 55 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
DC Current Gain					
at $-V_{CE} = 1\text{ V}$, $-I_C = 100\text{ mA}$	h_{FE}	100	-	250	-
MMBT8550C		160		400	
MMBT8550D		40		-	
at $-V_{CE} = 1\text{ V}$, $-I_C = 500\text{ mA}$					
Collector Base Cutoff Current	$-I_{CBO}$	-	-	100	nA
at $-V_{CB} = 35\text{ V}$					
Collector Base Breakdown Voltage	$-V_{(BR)CBO}$	40	-	-	V
at $-I_C = 10\text{ }\mu\text{A}$					
Collector Emitter Breakdown Voltage	$-V_{(BR)CEO}$	25	-	-	V
at $-I_C = 2\text{ mA}$					
Emitter Base Breakdown Voltage	$-V_{(BR)EBO}$	6	-	-	V
at $-I_E = 100\text{ }\mu\text{A}$					
Collector Emitter Saturation Voltage	$-V_{CE(sat)}$	-	-	0.5	V
at $-I_C = 500\text{ mA}$, $-I_B = 50\text{ mA}$					
Base Emitter Saturation Voltage	$-V_{BE(sat)}$	-	-	1.2	V
at $-I_C = 500\text{ mA}$, $-I_B = 50\text{ mA}$					
Gain Bandwidth Product	f_T	-	100	-	MHz
at $-V_{CE} = 5\text{ V}$, $-I_C = 10\text{ mA}$					






Kingtronics® International Company

Website: www.kingtronics.com

Email: info@kingtronics.com

Tel: (852) 8106 7033

Fax: (852) 8106 7099

Kingtronics®**MMBT8550****PNP Silicon Epitaxial Planar Transistors****RATINGS AND CHARACTERISTIC CURVES MMBT8550**

Note: Specifications are subject to change without notice.

Kingtronics® International CompanyWebsite: www.kingtronics.comEmail: info@kingtronics.com

Tel: (852) 8106 7033

Fax: (852) 8106 7099