

# PME-1210

## 1-phase Multifunction Power Meter

NEW



### Features

- Small size with 100mm depth
- Panel cut 92 x 46 mm
- Multi-function power measurement
- Modbus RTU protocol over RS-485

### Introduction

The PME-1210 is a 1-phase multi-function power meter for sub-metering applications, ranging from power distribution, small motor control to lighting load circuit. It measures current & voltage, KW, kwh, kwh and PF values. The measurement data can be viewed directly from local display, and also can be transmitted through a RS-485 using the Modbus protocol.

### Specifications

#### Voltage Measurement

- **Voltage** 80 ~ 350 V<sub>AC</sub>
- **Resolution/Accuracy** 0.1V/0.5% full scale
- **Permanet overload** 450 V<sub>AC</sub>
- **Transient Voltage** 2 x V<sub>in</sub> (1sec)

#### Current Measurement (Std. 5A CT)

- **Range** 5 mA ~ 5 A
- **Resolution** 1 mA
- **Starting Current** 5 mA
- **Permanent Overload** 10 A
- **Transient current** 20 x I<sub>in</sub> (1sec)
- **Accuracy** 0.5% full scale

#### Power Measurement

- **Resolution** 1W
- **Accuracy** 1% full scale

#### Energy Measurement

- **Display Resolution** 0.1 kWh (Range from 0 to 9,999,999.9kWh)
- **Record Resolution** 0.01 kWh (Range from 0 to 9,999,999.99kWh)
- **kWh Accuracy** 1% with PF 0.5 ~ 1.0

#### Frequency Measurement

- **Range** 45.0 to 65.0 Hz
- **Resolution/Accuracy** 0.1 Hz

#### PF Measurement

- **Range** 0.000 to 1.000
- **Resolution** 0.001 (polarized)
- **Accuracy** 1% (PF 0.5 ~ 1.0)

#### Front Panel Interface

- **Display** 6 digit 7 segment LED
- **Indicators** 8 LED
- **Mode** Display and Setting
- **Setting** 3 Function Key, ID address, Baud Rate, PT Ratio, CT Ratio

#### Communication Interface

- **Bus** RS-485, Photo Isolated
- **Protocol** Modbus/RTU (format: 8/N/1)
- **Baud Rate** 1200/2400/4800/9600
- **Meter ID** 0 ~ 254

#### Reliability

- **Communication** IEC61000-4-4 1 kV
- **Surge Test** IEC61000-4-5 4 kV
- **EFT Test** IEC61000-4-4 1 kV

#### AC Insulation

- **Aux. Power** 4.0 kV
- **Current Input** 4.0 kV

#### Power Supply

- **AC 110V** 93 ~ 126 V<sub>AC</sub>
- **AC 220V** 187 ~ 253 V<sub>AC</sub>

#### Physical

- **Operating Temperature** -10 ~ 70°C (32 ~ 158°F)
- **Operating Humidity** 0 ~ 90% RH non-condensing
- **Storage Humidity** 0 ~ 95% (Non-condensing)
- **Weight** 425g (Std. 5A CT)
- **Panel Cut** 92 x 46 mm
- **Dimensions (W x H x D)** 110 x 50 x 115 mm

### Ordering Information

- **PME-1210-AE** 1-phase Multifunction Power Meter

1

Motion Control

2

Hazardous Location

3

Energy Automation

4

Building Automation Systems

5

Automation Software

6

Operator Panels

7

Automation Panel PCs

8

Industrial Monitors

9

Industrial Ethernet

10

Device Servers & Gateways

11

Serial Communication Cards

12

Embedded Auto. Computers

13

PACs

14

M2M I/O

15

Distributed Nano Controllers

16

RS-485 I/O

17

Ethernet I/O

18

DAQ Boards