


FAST RECOVERY SILICON HIGH VOLTAGE RECTIFIER



PART NUMBER	PIV VOLTS	I _O AMPS @ 40° C	V _f @ 100 mA @ 25° C	I _r @ PIV @ 25° C	MAX SINGLE CYCLE SURGE CURRENT	T _{rr}
B1506-50	5000	.30A	10 V	1 uA	30 AMPS	100 nSec
B1506-70	7000	.15 A	18 V	1 uA	30 AMPS	100 nSec
B1506-100	10000	.10 A	23 V	1 uA	30 AMPS	100 nSec
B1506-120	12000	.10 A	23 V	1 uA	30 AMPS	100 nSec
B1506-150	15000	.10 A	38 V	1 uA	30 AMPS	100 nSec
B1506-200	20000	.10 A	45 V	1 uA	30 AMPS	100 nSec

EQUIV. TO BS780 - () EXCEPT RECOVERY TIME

SUFFIX "A" REPRESENTS AVALANCHE CHARACTERISTICS EX: B1506-100A

NOTE 1: RECOVERY TIME MEASURED ON STORED CHARGE METER @ 99.9 mA.

(203) 467-2591 TEL

(203) 469-5928 FAX

Email: Info@ edal.com

Internet: <http://www.edal.com>

EDAL industries, inc.

51 Commerce St. East Haven, CT 06512