



目录 <b>MAPX</b>	设变内容 <b>MODIFICATION</b>	日期 <b>DATE</b>

特性: Specifications:

电气: Electrical:

1. 接触阻抗: Contact Resistance:  
30 milliohms MAX
2. 耐电压: Dielectric With Standing Voltage:  
500 V AC AT Sea Level
3. 绝缘阻抗: Insulation Resistance:  
1000 MEGA ohms MIN

机构: Mechanical:

1. 结合力: Mating Force:  
35 N MAX 最大 35 N
2. 拔出力: Unmating Force:  
8 N MIN 最少 8 N

材料: Material:

1. 塑胶: 黑色PBT.
2. 端子: Contact: C2680, T= $0.25 \pm 0.01$
3. 外壳: Shell: SPCC, T= $0.3 \pm 0.01$

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area:  
Tin/Lead On Solder Talls. 接触点镀金1唛, 脚镀锡100唛
2. 外壳: Shell:  
Nickel Plating . 镀镍80唛  
额定电流2.5A, 盐雾24H, 镀锡部分12H

产品图 PRODUCT CHART DWG			
公差表 TOLERANCE UNLESS OTHERWISE			
尺寸	A	B	*C
0-5	$\pm 0.02$	$\pm 0.05$	$\pm 0.1$
5-10	$\pm 0.05$	$\pm 0.1$	$\pm 0.15$
10-50	$\pm 0.1$	$\pm 0.15$	$\pm 0.2$
未标注的公差按一般标准计算			

深圳市精拓金电子有限公司

单位 UNITS	司 MM	制图 DRAWING	客户料号 PRODUCT PART NO.	912-122A101AD10200		
比例 SCALE	1:1	审核 CHKD	产品名称 PRODUCT NO.	AF10.6短体前两脚无边铜壳PBT白胶8.2DIP		
日期 DATE	2014/04/23	核准 APPD	角法 VIEW	<table border="1"> <tr> <td>版本 VER</td> <td>A0</td> </tr> </table>	版本 VER	A0
版本 VER	A0					