



## Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors

## Complementary

Electrical connection	Straight female connector M12, 5 pins (included earth pin)
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	25 m
Cable outer diameter	5.9 mm
Cable composition	5 x 0.34 mm <sup>2</sup>
Wire insulation material	PUR
[Ue] rated operational voltage	30 V AC 36 V DC
[In] rated current	4 A
Contact resistance	5000 µOhm
Minimum insulating resistance	1 GΩ

## Environment




IP degree of protection	IP65 IP69K IP67
Product certifications	CULus
Ambient air temperature for operation	-40...80 °C static -5...80 °C flexing
Ambient air temperature for storage	-40...80 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	858 g
Package 1 Height	6.8 cm
Package 1 width	22.9 cm
Package 1 Length	22.8 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	898 g
Package 2 Height	5 cm
Package 2 width	21 cm

Package 2 Length	21 cm
Unit Type of Package 3	S02
Number of Units in Package 3	5
Package 3 Weight	4.536 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#"> EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#"> Yes</a>