


Sales Region	USA/China/ASEAN/India
Series	PHV
Model	
Status	 Production
Option	Positive polarity
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	104 to 126VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	300000Vdc
Output Voltage Range[DC]	0 to 300000V
Rated Output Current	1mA
Output Current	0 to 1mA
Rated Output Power	350W
Polarity	Positive
Power Factor	0.72
Efficiency	90% Typ.
Voltage Ripple Noise	30.05V

Package Type & Size

Package / Mounting	Cabinet type
Width(W)	600mm Nom. (23.62in Nom.)
Height(H)	2000mm Nom. (78.74in Nom.)
Depth(D)	600mm Nom. (23.62in Nom.)
Weight	200kg Typ. (440.9lbs Typ.)

Other

Operating Temp. Range	0 to 40°C
Storage Temp. Range	0 to 40°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	EN61010-1 CE Mark
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.