
STS2DNF30L

Dual N-channel 30V - 0.09Ω - 3A SO-8 STripFET™ Power MOSFET

General features

Type	V_{DSS}	$R_{DS(on)}$	I_D
STS2DNF30L	30V	<0.011Ω	3A

- Standard outline for easy automated surface mount assembly
- Low threshold gate drive




S0-8

Description

This Power MOSFET is the latest development of STMicroelectronics unique "Single Feature Size™" strip-based process. The resulting transistor shows extremely high packing density for low on-resistance, rugged avalanche characteristics and less critical alignment steps therefore a remarkable manufacturing reproducibility.

Internal schematic diagram



Applications

- Switching application

Order codes

Part number	Marking	Package	Packaging
STS2DNF30L	S2DNF30L	SO-8	Tape & reel

Contents

1 Electrical ratings 3

2 Electrical characteristics 4

2.1 Electrical characteristics (curves) 6

3 Test circuit 8

4 Package mechanical data 9

5 Revision history 11

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage (v_{gs} = 0)	30	V
V_{GS}	Gate- source voltage	±18	V
I_D	Drain current (continuos) at T_C = 25°C	3	A
I_D	Drain current (continuos) at T_C = 100°C	1.9	A
I_{DM} (1)	Drain current (pulsed)	9	A
P_{TOT}	Total dissipation at T_C = 25°C dual operation Total dissipation at T_C = 25°C single operation	1.6 2	W W
T_{stg}	Storage temperature	-55 to 150	°C
T_j	Max. operating junction temperature	150	°C

1. Pulse width limited by safe operating area

Table 2. Thermal data

$R_{thj\text{-}a}$	Thermal resistance junction-ambient Max single operation Thermal resistance junction-ambient Max dual operation	62.5 78	°C/W °C/W
T_J	Maximum operating junction ambient	150	°C
T_{stg}	Storage temperature	-55 to 175	°C

2 Electrical characteristics

(T_{CASE}=25°C unless otherwise specified)

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source Breakdown voltage	I_D = 250 µA, V_{GS} = 0	30			V
I_{DSS}	Zero gate voltage Drain current (V_{GS} = 0)	V_{DS} = Max rating			1	µA
		V_{DS}=Max rating, T_C=125°C			10	µA
I_{GSS}	Gate-body leakage current (V_{DS} = 0)	V_{GS} = ±18V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250µA	1	1.7	2.5	V
$R_{DS(on)}$	Static drain-source on resistance	V_{GS} = 10V, I_D = 1A		0.09	0.011	Ω
		V_{GS} = 5V, I_D = 1A		0.13	0.15	Ω

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
g_{fs} (1)	Forward transconductance	V_{DS}>$I_{D(on)}$x$R_{DS(on)max}$ I_D=2.5A		2.5		S
C_{iss}	Input capacitance	V_{DS} = 25V, f = 1 MHz, V_{GS} = 0		121		pF
C_{oss}	Output capacitance			45		pF
C_{rss}	Reverse transfer capacitance			11		pF
Q_g	Total gate charge	V_{DD} = 24V, I_D = 2A, V_{GS} = 10V		4.5		nC
Q_{gs}	Gate-source charge			1.7		nC
Q_{gd}	Gate-drain charge			0.9		nC

1. Pulsed: Pulse duration = 300 µs, duty cycle 1.5.

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD}=15 V, I_D=1A, R_G=4.7Ω, V_{GS}= 4.5V (see Figure 12)		19		ns
t_r	Rise time			20		ns
$t_{d(off)}$	Turn-off delay time	V_{DD}=15 V, I_D=1A, R_G=4.7Ω, V_{GS}= 4.5V (see Figure 12)		12		ns
t_f	Fall time			8		ns

Table 6. Source drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max	Unit
I_{SD}	Source-drain current				3	A
I_{SDM} (1)	Source-drain current (pulsed)				12	A
V_{SD} (2)	Forward on voltage	I_{SD} = 2A, V_{GS} = 0			1.3	V
t_{rr} Q_{rr} I_{RRM}	Reverse recovery time Reverse recovery charge Reverse recovery current	I_{SD} = 2A, V_{DD} = 30V di/dt = 100A/µs, T_j = 150°C (see Figure 14)		19 8.1 0.85		ns nC A

1. Pulse width limited by safe operating area.
2. Pulsed: Pulse duration = 300 µs, duty cycle 1.5%

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characteristics




Figure 4. Transfer characteristics




Figure 5. Transconductance




Figure 6. Static drain-source on resistance




Figure 7. Gate charge vs. gate-source voltage




Figure 8. Capacitance variations




Figure 9. Normalized gate threshold voltage vs. temperature




Figure 10. Normalized on resistance vs. temperature





Figure 11. Source-drain diode forward characteristics



3 Test circuit

Figure 12. Switching times test circuit for resistive load




Figure 13. Gate charge test circuit




Figure 14. Test circuit for inductive load switching and diode recovery times




Figure 15. Unclamped Inductive load test circuit




Figure 16. Unclamped inductive waveform





Figure 17. Switching time waveform




4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at : *www.st.com*

SO-8 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.75			0.068
a1	0.1		0.25	0.003		0.009
a2			1.65			0.064
a3	0.65		0.85	0.025		0.033
b	0.35		0.48	0.013		0.018
b1	0.19		0.25	0.007		0.010
C	0.25		0.5	0.010		0.019
c1	45 (typ.)					
D	4.8		5.0	0.188		0.196
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		3.81			0.150	
F	3.8		4.0	0.14		0.157
L	0.4		1.27	0.015		0.050
M			0.6			0.023
S	8 (max.)					



5 Revision history

Table 7. Revision history

Date	Revision	Changes
21-Jun-2004	3	Complete document
10-Nov-2006	4	The document has been reformatted
31-Jan-2007	5	Typo mistake on *Table 1*.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com