



Frontier Electronics Corp.





667 E. COCHRAN STREET, SIMI VALLEY, CA 93065
 TEL: (805) 522-9998 FAX: (805) 522-9989
 E-mail: frontiersales@frontierusa.com
 Web: frontierusa.com

CCFL Inverter Transformer—SEC2021-01

A. Electrical specification:

Part No.	Marking	Suitable Frequency	Max. Open Voltage	Max. Lamp Watt.	Efficiency
SEC2021-01	SEC2021-01	40KHz~200KHz	1600Vrms	6W	80%

B. Schematics and Mechanical dimensions: (Unit: mm)



Turn Ratio:
 $N1 : N3 = N2 : N3 = 1 : 233.33$

C. Electrical Data:

Winding	Start	Finish	L (@ 1KHz,1.0V)	Lk (@ 1KHz,1.0V)	DCR Ω (@25°C)
N1	3	2	11.5 μ H \pm 15 %		0.070 Max.
N2	2	1	11.5 μ H \pm 15 %		0.070 Max.
N3	8	9	480 mH \pm 10 %	228 mH \pm 10 %	1200 Max.

D. Insulation:

Term	Item	Spec.	Condition
Hi-Pot	N1 & N2 to N3	1200 VAC / 1 Minute	@Cut off current=5mA
	N1, N 2 & N3 to Core		
Isolation	N1 & N2 to N3	100 M-OHM MIN.	@500 VDC
	N1, N 2 & N3 to Core		

E. Features:

- Low profile height: Maximum 7.0mm.
- High efficiency.
- Surface mount.
- Suitable for standard IR re-flows soldering.

F. Uses:

- Black Light power supplies transformer available.
- Personal Computer.

Note: RoHS compliant; for the ROHS parts, we add “-LFR” at the end of the P/N.