
SAW Bandpass Filter F9472

Features

- RF bandpass filter
- High attenuation
- Usable bandwidth 25MHz
- No matching 50Ω single-ended operation
- Ceramic Surface Mounted Device (SMD) Package

Package Dimensions



Dimensions shown are nominal in millimeters

Body : Al_2O_3 Ceramic
Lid : Kovar, Ni Plated
Terminations : Au plating 0.3 ~ 1.0 um, Over a 1.27 ~ 8.89 um
Ni Plating

Pin Configuration	
2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameter	**Unit**	**Minimum**	**Typical**	**Maximum**
Operating Temperature Range	°C	-10	25	60
Storage Temperature Range	°C	-40	-	85
Power Handling Capability	dBm	-	-	-

Electrostatics Sensitive Device (**ESD**)

SAW Bandpass Filter F9472

Preliminary specifications

Fc = 947.5MHz

Terminating source impedance : 50Ω

Terminating load impedance : 50Ω

		Minimum	Typical	Maximum
Center Frequency (Fc)	MHz	-	947.5	-
Insertion Loss (Fc +/- 12.5 MHz)	dB	-	3.5	4.0
Amplitude Ripple (Fc +/- 12.5 MHz)	dB	-	0.5	2.0
Absolute Group Delay at Fc	nsec	-	35	-
Group Delay Variation (Fc +/- 12.5 MHz)	nsec	-	15	-
VSWR (Fc +/- 12.5 MHz)		-	1.5	2.0
Relative Attenuation … ~ Fc - 45 MHz Fc + 80 MHz ~ …	dB	 40 40	 50 50	 -
Temperature Coefficient of Frequency	ppm/°C	-	-80	-

Notes :


1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.

2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances

3) All attenuation measurements are measured relative to insertion loss

Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

ITF[1)]


9472[2)]


1) Manufacturer name

2) Marking Number

* Ink or Laser Marking available


Typical Performance (at 25℃)







SAW Bandpass Filter F9472


Input / Output VSWR Charts





Input / Output Smith Charts






Packing Specification


1. Reeling Quantity : 1000 pcs / reel

2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification



2. Tensile strength of carrier tape


4.4N/mm width

3. Top cover tape adhesion

1) pull off angle : 0~15°


2) speed : 300mm/min

3) force : 20~70g




SAW Bandpass Filter F9472

Carrier Tape Dimensions [unit : mm]




A	4.30 ± 0.1
B	4.30 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]



Integrated Technology Future	**I T F Co., Ltd.** 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyounggi-Do, Korea 421-809	Part No.	F9472
		Rev. Date	2004-11-01
		Rev.	DR3008-PS02 7/7