

REVISION			
REV.	DESCRIPTION	DATE	APPROVED





NOTES:

1. CABLE: UL20276
   28AWGx1P+DW+FOIL)x7+28AWGx3C+28AWGx1P+MYLAR+FOIL+BD
   OUTER JACKET COLOR: BEIGE, OD: 8.5 ± 0.3mm
   PRINTING: E166307 AWM 20276 28AWG 80˚C 30V VW-1
   LOW VOLTAGE COMPUTER CABLE
2. CONNECTORS: DVI(24+1)P/M TO DVI(24+1)P/M
3. HOOD: ASS'Y TYPE, COLOR: BEIGE
4. ELECTRICAL TEST:
   <1>.100% OPEN SHORT & MISS WIRE TEST
   <2>. INSULATION RESISTANCE: DC400V 10M ohm MIN.
   <3>. CONDUCTOR RESISTANCE: 3 ohm MAX.
5. PACKING: 1PC/POLYBAG

No.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARKS
①	DVI (24+1)P/M - CONTACT	BRASS / GOLD PLATED SOLDER TYPE	50	
②	DVI (24+1)P/M - INSULATOR	THERMOPLASTIC / BLACK UL94V-0	2	
③	DVI (24+1)P/M - SHELL	NICKEL PLATED	2	
④	CAN	STEEL TIN PLATED ID: 9.0mm	2	
⑤	DVI (24+1)P/M - COVER	45P PVC/COLOR: BEIGE	2	
⑥	THUMB SCREW	#4-40 2.8x45mm, NICKEL PLATED	4	
⑦	SCREW - MOLD	35P PVC / COLOR: BEIGE	4	
⑧	CABLE DVI 24+1 UL 20276	KL 3007ABK01A	1	
⑨	MINI TIE	PE/BLACK	2	
⑩	POLYBAG	0.08x220x260	1	

Dim range (mm)	Tolerance +/- (mm)
0-1	0.15
1-6	0.20
6-18	0.30
18-50	0.50
50-120	0.70
120-250	0.90
250-500	1.20

Qualtek Electronics Corp.
WCI DIVISION

Part Number: 1321028-10 RoHS Compliant

Description: DVI (24+1)P/M - DVI (24+1)P/M

Drawn / Date	Checked / Date	Approved / Date
B. Grubb 01-25-07	01-25-07	JJH / 01-25-07