

# 产品规格书

批准	审核	校核	编制
纪春华	朴致均	赵宇辉	郑羿
2019.02.14	2019.02.14	2019.02.14	2019.02.14

规格书更改履历:

序号	更改内容	履历号	更改时间	责任人
1	新规制定	000	2019.02.14	郑羿



## SOT-23 Plastic-Encapsulate Diodes

### BAV70 SWITCHING DIODES

#### FEATURES

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance

**MARKING: A4**







#### Maximum Ratings @Ta=25℃

Parameter	Symbol	Limit	Unit
Reverse Breakdown Voltage	$V_{RM}$	70	V
DC Blocking Voltage	$V_R$	70	V
Forward Current	$I_F$	200	mA
Repetitive Peak Forward Current	$I_{FRM}$	500	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	$I_{FSM}$	2.0	A
Power Dissipation	$P_D$	225	mW
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	556	℃/W
Junction Temperature	$T_J$	150	℃
Storage Temperature range	$T_{STG}$	-55~+150	℃

#### Electrical Characteristics @Ta=25℃

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Reverse breakdown voltage	$V_R$	70			V	$I_R=100\mu A$
Forward voltage	$V_{F1}$			0.715	V	$I_F=1mA$
	$V_{F2}$			0.855	V	$I_F=10mA$
	$V_{F3}$			1	V	$I_F=50mA$
	$V_{F4}$			1.25	V	$I_F=150mA$
Reverse current	$I_R$			2.5	$\mu A$	$V_R=70V$
Capacitance between terminals	$C_T$			1.5	pF	$V_R=0, f=1MHz$
Reverse recovery time	$t_{rr}$			6	ns	$I_F = I_R = 10mA,$ $I_{rr} = 0.1 \times I_R, R_L = 100K$



## Typical Characteristics

**Forward Characteristics**

**Reverse Characteristics**

**Capacitance Characteristics**

**Power Derating Curve**


## PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT-23



UNIT	A	B	b <sub>p</sub>	C	D	E	HE	A <sub>1</sub>	L <sub>p</sub>
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20

**The AUK Dalian Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).**

**Please make sure that you consult with us before you use these AUK Dalian Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Dalian Corp. cannot accept liability to any damage which may occur in case these AUK Dalian Corp. products were used in the mentioned equipments without prior consultation with AUK Dalian Corp..**

**Specifications mentioned in this publication are subject to change without notice.**