

ZWD100PAF-0524/TA



| | |
|-------------------------------|--|
| Sales Region | Worldwide |
| Series | ZWD-PAF |
| Status | Production |
| Feature | Peak power capability |
| Option | With cover type With terminal (Vertical) type |
| Option Lineup | Please refer to here. |
| Recommended EMC Filter | Please refer to here. |
| Accessories | Please refer to the catalog |



Electrical Characteristics

| | |
|-------------------------------------|---|
| Input Voltage Range[AC] | 85 to 265V |
| Input Voltage Range[DC] | 120 to 370V |
| Efficiency | 81% Typ. |
| Rated Output Voltage[DC] | <u>5V</u> <u>24V</u> |
| Output Voltage Range[DC] | <u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u> |
| Minimum Output Current | |
| Maximum Output Current | <u>5A</u> <u>4A</u> |
| Maximum Average Current | |
| Maximum Peak Current | |
| Total Maximum(Average) Output Power | 100W |
| Total Maximum Peak Power | 196W |

Cases Shape & Size

| | |
|---------------|------------|
| Case'□' shape | PC board |
| Width(W) | 85mm Nom. |
| Height(H) | 46mm Nom. |
| Depth(D) | 252mm Nom. |
| Weight | 780g Typ. |

Other

| | |
|----------------------------|---|
| Operating Temp. Range | -10 to 60°C |
| Cooling | Convection cooling |
| Safety Standard(Certified) | UL60950-1 CSA C22.2 No.60950-1 EN60950-1 EN50178 |
| Safety Standard(Conformed) | Den-an |

