Extract from the online catalog

UK 20,6-J HESILED

Order No.: 3211087



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3211087

Lever-type fuse terminal block

Commercial data	
GTIN (EAN)	4 046356 175074
Note	Made-to-order
sales group	A040
Pack	6 pcs.
Customs tariff	85363030
Catalog page information	Page 373 (CL-2009)

Product notes

WEEE/RoHS-compliant since: 01/01/2007

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Number of connections	2
Color	black
Insulating material	PA
Inflammability class acc. to UL 94	V0

Dimensions

Width	35.5 mm
Length	115 mm
Height NS 35/7.5	85.5 mm
Height NS 35/15	78 mm

Technical data

Fuse	Class J / 20.6 x 57
Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	III b
Nominal voltage U_N	600 V (the current and voltage are determined by the fuse)

Connection data

Conductor cross section solid min.	2.5 mm²
Conductor cross section solid max.	50 mm²
Conductor cross section stranded min.	2.5 mm²
Conductor cross section stranded max.	50 mm²
Conductor cross section AWG/kcmil min.	14
Conductor cross section AWG/kcmil max	1
Conductor cross section stranded, with ferrule without plastic sleeve min.	2.5 mm²
Conductor cross section stranded, with ferrule without plastic sleeve max.	50 mm²
Conductor cross section stranded, with ferrule with plastic sleeve min.	2.5 mm²
Conductor cross section stranded, with ferrule with plastic sleeve max.	50 mm²
2 conductors with same cross section, solid min.	2.5 mm²
2 conductors with same cross section, solid max.	16 mm²
2 conductors with same cross section, stranded min.	2.5 mm²
2 conductors with same cross section, stranded max.	16 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	2.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	16 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	2.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	16 mm²
Type of connection	Screw connection
Stripping length	20 mm
Screw thread	M6
Tightening torque, min	3.5 Nm
Tightening torque max	4 Nm

Certificates / Approvals


Certification	CSA, CUL Listed, UL Listed

Accessories

Item	Designation	Description
Assembly		
3022218	CLIPFIX 35	Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 DIN rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray
0801762	NS 35/ 7,5 CU UNPERF 2000MM	DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m
0801733	NS 35/ 7,5 PERF 2000MM	DIN rail, material: Steel, galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2 m
0801681	NS 35/ 7,5 UNPERF 2000MM	DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m
1201756	NS 35/15 AL UNPERF 2000MM	DIN rail, deep-drawn, high profile, unperforated, 1.5 mm thick, material: Aluminum, height 15 mm, width 35 mm, length 2 m
1201895	NS 35/15 CU UNPERF 2000MM	DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m
1201730	NS 35/15 PERF 2000MM	DIN rail, material: Steel, perforated, height 15 mm, width 35 mm, length: 2 m
1201714	NS 35/15 UNPERF 2000MM	DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m
1201798	NS 35/15-2,3 UNPERF 2000MM	DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

Diagrams/Drawings

Circuit diagram



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg,Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
http://www.phoenixcontact.de

© 2011 Phoenix Contact
Technical modifications reserved;