



# Female MAXI™ Fuse

## Time Delay, 20-60 Amp

FMX



### Female FMX Maxi™ – Fuse

Time Delay

The FMX is available in ampere ratings from 20 - 60A in a standard 27 mm height. Use 5.5 mm blade centers with a 6.0 mm width and .81 mm thick blades.

Part No.	Amp Rating	Color	Part No.	Amp Rating	Color
FMX-20	20	Lt. Blue	FMX-50	50	Red
FMX-30	30	Pink	FMX-60	60	Yellow
FMX-40	40	Green			

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Cooper Bussmann:

[FMX-20](#) [FMX-30](#) [FMX-50](#) [FMX-40](#) [FMX-25LP](#) [BP/FMX-40](#) [FMX-50LP](#) [BP/FMX-50](#) [BP/FMX-20](#) [BK/FMX-30](#)  
[FMX-60LP](#) [FMX-40LP](#) [BP/FMX-30](#) [FMX-20LP](#) [FMX-30LP](#)