

ZUP10-40



Sales Region	Worldwide
Series	ZUP
Type	400W Model
Status	Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage[AC]	Single-phase 100V/200V
Input Voltage Range[AC]	85 to 265V
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	10V
Output Voltage[DC]	0 to 10V
Rated Output Current	40A
Output Current	0 to 40A
Rated Output Power	400W
Efficiency	82% Typ.
Voltage Ripple Noise	0.005Vrms (5Hz to 1MHz)
Current Ripple Noise	0.05Arms (5Hz to 1MHz)

Cases Shape & Size

Case'□ shape	Bench top
Width(W)	70mm Nom.
Height(H)	124mm Nom.
Depth(D)	350mm Nom.
Weight	3200g Typ.

Other

Interface Option	
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	CSA C22.2 No.1010.1-92 EN61010-1 UL3111-1
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

† Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.