2018-03-23
Product version 02
Document revision 0

Data sheet

Order No.: 1803523

Type: MCV 1,5/12-G-3,81

Header



The figure shows a 10-position version of the product

1 Main features



- No. of pos. 12
- Nominal cross section 1.5 mm²
- Color green
- Pitch 3.81 mm
- Mounting type Wave soldering
- Nominal current 8 A
- Nominal voltage 160 V
- Connection direction 90 °
- Type of packaging packed in cardboard

2 Your advantages

- Well-known mounting principle allows worldwide use
- Vertical connection enables multi-row arrangement on the PCB
- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies

Make sure you always use the latest documentation.
It can be downloaded at: phoenixcontact.net/product/1803523


© PHOENIX CONTACT 2018

3 Table of contents

1 Main features ... 1
2 Your advantages ... 1
3 Table of contents ... 2
4 3D model in PDF can be activated (Acrobat Reader only) ... 3
5 item properties ... 4
5.1 Material data ... 4
6 Dimensions ... 4
6.1 Dimensions for the product ... 4
6.2 Dimensions for PCB design ... 4
7 Series drawing ... 5
8 Packaging information ... 6
9 Application ... 6
9.1 Temperature limit values ... 6
10 Mechanical tests ... 7
11 Electrical tests ... 8
11.1 Electrical data ... 8
11.2 Air and creepage distances ... 8
12 Current carrying capacity/derating curves ... 9
13 Environmental and durability tests ... 11
13.1 Vibration test ... 11
14 Classification for connectors ... 11
15 Approvals ... 11
16 Commercial Data ... 13
17 corresponding plugs ... 13
18 Accessories ... 13
19 Combination tests ... 14

© PHOENIX CONTACT 2018

4 3D model in PDF can be activated (Acrobat Reader only)



© PHOENIX CONTACT 2018

5 item properties

Order No.	1803523
Type	MCV 1,5/12-G-3,81
Type of contact	Male connector
Range of articles	MCV 1,5/..-G
Pitch	3.81 mm
Number of positions	12
Locking	without
Mounting type	Wave soldering
Pin layout	Linear pinning

5.1 Material data

Material of metal parts		
Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201	
Contact material	Cu alloy	
Surface contact area	Ni 1 µm ... 3 µm , Sn 3 µm ... 5 µm	
Soldering area surface	Ni 1 µm ... 3 µm , Sn 3 µm ... 5 µm	
Surface characteristics	Tin-plated	

Insulating material data	Housing	Housing
Insulating material	PBT	
CTI according to IEC 60112	225	
Flammability rating according to UL 94	V0	
Color	green (6021)	

6 Dimensions

6.1 Dimensions for the product

Length	7.25 mm
Width	47.11 mm
Height (without solder pin)	9.2 mm
Total height	12.6 mm
Solder pin [P]	3.4 mm
Dimension a	41.91 mm


6.2 Dimensions for PCB design

Hole diameter	1.2 mm
Pin dimensions	0,8 x 0,8 mm

© PHOENIX CONTACT 2018

1803523 MCV 1,5/12-G-3,81

7 Series drawing



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless expressed is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

© PHOENIX CONTACT 2018

8 Packaging information

Type of packaging	packed in cardboard
Pieces per package	50

9 Application

9.1 Temperature limit values

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C (dependent on the derating curve)

© PHOENIX CONTACT 2018

10 Mechanical tests

Mechanical test group A	
Specification	IEC 61984:2008-10
Visual examination	Test passed
Specification	IEC 60512-1-1:2002-02
Dimensional test	Test passed
Specification	IEC 60512-1-2:2002-02
Resistance of marking	Test passed
Specification	IEC 60068-2-70:1995-12
Insertion and withdrawal force	Test passed
Specification	IEC 60512-13-2:2006-02
No. of cycles	25
Insertion strength per pos. approx.	8 N
Withdraw strength per pos. approx.	6 N
Polarization and coding	Test passed
Specification	IEC 60512-13-5:2006-02
Test force	20 N
Contact retention in insert	Test passed
Specification	IEC 60512-15-1:2008-05
Test force per pos.	29.5 N

© PHOENIX CONTACT 2018

11 Electrical tests

11.1 Electrical data

Rated current / conductor cross section	8 A / 1.5 mm²
Rated insulation voltage (III/2)	160 V
Rated surge voltage (III/2)	2.5 kV
Contact resistance	1.2 mΩ
Degree of pollution	2

11.2 Air and creepage distances


Component	Header		
Specification	IEC 60664-1:2007-04		
Mains type	unearthed mains		
Insulating material group	IIIa		
Comparative tracking index (IEC 60112:2003-01)	CTI 225		
Rated insulation voltage	160 V	160 V	250 V
Rated surge voltage	2.5 kV	2.5 kV	2.5 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	1.5 mm	1.5 mm	1.5 mm
Minimum value of the creepage path requirement in acc. with table	2.5 mm	1.6 mm	2.5 mm

© PHOENIX CONTACT 2018


12 Current carrying capacity/derating curves

Specification	IEC 61984:2008-10
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	0.8
Number of positions	See diagram
Conductor cross section	1.5 mm²
Note	


Type: MC 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81



Type: FRONT-MC 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81




Type: FK-MCP 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81



© PHOENIX CONTACT 2018

1803523 MCV 1,5/12-G-3,81

Type: FMC 1,5/...-ST-3,81 with MCV 1,5/...-G-3,81



© PHOENIX CONTACT 2018

13 Environmental and durability tests

13.1 Vibration test

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	5 g (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

14 Classification for connectors

Specification	IEC 61984:2008-10
Main features	Connectors without switching capacity (COC)
Construction form	Fixed connectors
Strain relief elements	without strain relief
Protection against electric shock	Not encapsulated - touch-proof when inserted
Protection class	
Protective conductor	without PE
Lock	no

15 Approvals

CSA				
Use group	B	D		
mm²/AWG/kcmil				
Voltage	300 V	300 V		
Current	8 A	8 A		

VDE Gutachten mit Fertigungsüberwachung				
mm²/AWG/kcmil				
Voltage	160 V			
Current	8 A			

IECEE CB Scheme				
mm²/AWG/kcmil				
Voltage	160 V			
Current	8 A			

CCA				
mm²/AWG/kcmil				
Voltage	160 V			
Current	8 A			

© PHOENIX CONTACT 2018

1803523 MCV 1,5/12-G-3,81

cULus Recognized				
Use group	B	D		
mm²/AWG/kcmil				
Voltage	300 V	300 V		
Current	8 A	8 A		

EAC

© PHOENIX CONTACT 2018

16 Commercial Data

Order No.	1803523
Type	MCV 1,5/12-G-3,81
Pieces per package	50
Net weight	3.3 g
GTIN	4017918045838
	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

17 corresponding plugs





Order No.	Type
1748079	FMC 1,5/12-ST-3,81
1803675	MC 1,5/12-ST-3,81
1827075	MCVW 1,5/12-ST-3,81
1827224	MCVR 1,5/12-ST-3,81
1850767	FRONT-MC 1,5/12-ST-3,81
1851148	FK-MCP 1,5/12-ST-3,81
1852273	MCC 1/12-STZ-3,81
1897490	QC 0,5/12-ST-3,81

18 Accessories

Description	Order No.	Type
	0804109	SK 3,81/2,8:FORTL.ZAHLEN
Coding profile, is inserted into the slot on the plug or inverted header, red insulating material	1734634	CP-MSTB
	0805399	SK 3,81/2,8:UNBEDRUCKT
	0805056	SK 3,81/2,8:SO
	0804141	SK 3,81/2,8: 1-250
Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm	1051993	B-STIFT

© PHOENIX CONTACT 2018

19 Combination tests

					
	MCV 1,5/..-G	**MC 1,5/..-ST**	**FRONT-MC 1,5/..-ST**	**FK-MCP 1,5/..-ST**	**FMC 1,5/..-ST**
Specification	IEC 61984	IEC 61984	IEC 61984	IEC 61984	IEC 61984
Mechanical tests (A)					
Insertion/withdrawal force per position	approx. 8 N / 6 N	approx. 7 N / 5 N	approx. 9 N / 7 N	approx. 8 N / 5 N
Polarization when inserted Requirement >20 N	Test passed	Test passed	Test passed	Test passed
Contact holder in insert Requirements >20 N	Test passed	Test passed	Test passed	Test passed
Durability tests (B)					
Contact resistance R_1	1.2 mΩ	1.6 mΩ	1.6 mΩ	1.5 mΩ
Insertion/withdrawal cycles	25	25	25	25
Contact resistance R_2	1.2 mΩ	1.7 mΩ	1.6 mΩ	1.7 mΩ
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	2.95 kV	2.95 kV	2.95 kV	2.95 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV	1.39 kV	1.39 kV	1.39 kV
Insulation resistance Requirements > 5 MΩ	> 11 TΩ	> 5 TΩ	> 50 GΩ	> 50 GΩ
Thermal tests (C)					
Tested number of positions	20	20	20	20
Tested conductor cross section	1.5 mm^2	1.5 mm^2	1.5 mm^2	1.5 mm^2
Test current	8 A DC	8 A DC	8 A	8 A
Upper limiting temperature Requirements < 100°C	Test passed	Test passed	Test passed	Test passed
Climatic tests (D)					
Test sequence 1: low temperature storage	-40 °C/2 h	-40 °C/2 h	-40 °C/2 h	-40 °C/2 h
Test sequence 2: heat storage	100 °C/168 h	100 °C/168 h	100 °C/168 h	100 °C/168 h
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle	0.2 dm^3 SO_2 on 300 dm^3/ 40 °C/1 cycle
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 µs)	2.95 kV	2.95 kV	2.95 kV	2.95 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	1.39 kV	1.39 kV	1.39 kV	1.39 kV
Environmental and endurance tests (E)					
Specification	IEC 61984:2008-10	IEC 61984:2008-10	IEC 61984:2008-10	IEC 61984:2008-10
Degree of protection	Finger safety with IP20 test finger	Finger safety with IP20 test finger	Finger safety with IP20 test finger	Finger safety with IP20 test finger

© PHOENIX CONTACT 2018