Data Sheet June 1999 File Number 4447.4

100A, 55V, 0.008 Ohm, N-Channel, Power MOSFETs

These are N-Channel enhancement mode silicon gate power field effect transistors. They are advanced power MOSFETs designed, tested, and guaranteed to withstand a specified level of energy in the breakdown avalanche mode of operation. All of these power MOSFETs are designed for applications such as switching regulators, switching converters, motor drivers, relay drivers, and drivers for high power bipolar switching transistors requiring high speed and low gate drive power. These types can be operated directly from integrated circuits.

NOTE: Calculated continuous current based on maximum allowable junction temperature. Package limited to 75A continuous, see Figure 9.

Ordering Information

PART NUMBER	PACKAGE	BRAND
HRF3205	TO-220AB	HRF3205
HRF3205S	TO-263AB	HRF3205S

NOTE: When ordering, use the entire part number. Add the suffix T to obtain the TO-263AB variant in tape and reel, e.g., HRF3205ST.

Features

- 100A, 55V (See Note)
- Low On-Resistance, $r_{DS(ON)} = 0.008\Omega$
- Temperature Compensating PSPICE® Model
- Thermal Impedance SPICE Model
- UIS Rating Curve
- Related Literature
  - TB334, “Guidelines for Soldering Surface Mount Components to PC Boards”

Symbol



Packaging

JEDEC TO-220AB



JEDEC TO-263AB



CAUTION: These devices are sensitive to electrostatic discharge; follow proper ESD Handling Procedures.
PSPICE® is a registered trademark of MicroSim Corporation.
http://www.intersil.com or 407-727-9207 | Copyright © Intersil Corporation 1999

Absolute Maximum Ratings $T_C = 25^oC$, Unless Othewise Specified

Drain to Source Voltage (Note 1)	V_{DSS}	55	V
Drain to Gate Voltage (R_{GS} = 20kΩ) (Note 1)	V_{DGR}	55	V
Gate to Source Voltage	V_{GS}	±20V	V
Drain Current			
Continuous	I_D	100	A
Pulsed Drain Current (Note 2)	I_{DM}	390	A
Pulsed Avalanche Rating	E_{AS}	Figure 10	
Power Dissipation	P_D	175	W
Derate Above 25^oC		1.17	$W/^oC$
Operating and Storage Temperature	T_J, T_{STG}	-55 to 175	^oC
Maximum Temperature for Soldering			
Leads at 0.063in (1.6mm) from Case for 10s	T_L	300	^oC
Package Body for 10s, See Techbrief 334	T_{pkg}	260	^oC

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

NOTE:

1. $T_J = 25^oC$ to 150^oC.

Electrical Specifications $T_C = 25^oC$, Unless Otherwise Specified

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNITS
Drain to Source Breakdown Voltage	BV_{DSS}	I_D = 250μA, V_{GS} = 0V		55	-	-	V
Gate to Source Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 250μA		2	-	4	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 55V, V_{GS} = 0V		-	-	25	μA
		V_{DS} = 44V, V_{GS} = 0V, $T_C = 150^oC$		-	-	250	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS} = ±20V		-	-	100	nA
Breakdown Voltage Temperature Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	Reference to 25^oC, I_D = 250μA		-	0.057	-	V
Drain to Source On Resistance	$r_{DS(ON)}$	I_D = 59A, V_{GS} = 10V (Figure 4)		-	0.0065	0.008	Ω
Turn-On Delay Time	$t_{d(ON)}$	V_{DD} = 28V, $I_D \cong$ 59A, R_L = 0.47Ω, V_{GS} = 10V, R_{GS} = 2.5Ω		-	14	-	ns
Rise Time	t_r			-	100	-	ns
Turn-Off Delay Time	$t_{d(OFF)}$			-	43	-	ns
Fall Time	t_f			-	70	-	ns
Total Gate Charge	Q_g	V_{DD} = 44V, $I_D \cong$ 59A, V_{GS} = 10V, $I_{g(REF)}$ = 3mA (Figure 6)		-	-	170	nC
Gate to Source Charge	Q_{gs}			-	-	32	nC
Gate to Drain "Miller" Charge	Q_{gd}			-	-	74	nC
Input Capacitance	C_{ISS}	V_{DS} = 25V, V_{GS} = 0V, f = 1MHz (Figure 5)		-	4000	-	pF
Output Capacitance	C_{OSS}			-	1300	-	pF
Reverse Transfer Capacitance	C_{RSS}			-	480	-	pF
Internal Source Inductance	L_S	Measured From the Contact Screw on Tab to Center of Die	Modified MOSFET Symbol Showing the Internal Devices Inductances	-	7.5	-	nH
		Measured From the Drain Lead, 6mm (0.25in) From Package to Center of Die					
Internal Drain Inductance	L_D	Measured From the Source Lead, 6mm (0.25in) From Header to Source Bonding Pad		-	4.5	-	nH
Thermal Resistance Junction to Case	$R_{\theta JC}$			-	-	0.85	$^oC/W$
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	TO-220		-	-	62	$^oC/W$
		TO-263 (PCB Mount, Steady State)		-	-	40	$^oC/W$



Source to Drain Diode Specifications

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Continuous Source to Drain Current	I_{SD}	MOSFET Symbol Showing The Integral Reverse P-N Junction Diode 	-	-	100 (Note 1	A
Pulsed Source to Drain Current (Note 2)	I_{SDM}		-	-	390	A
Source to Drain Diode Voltage	V_{SD}	I_{SD} = 59A (Note 4)	-	-	1.3	V
Reverse Recovery Time	t_{rr}	I_{SD} = 59A, dI_{SD}/dt = 100A/µs (Note 4)	-	110	170	ns
Reverse Recovered Charge	Q_{RR}	I_{SD} = 59A, dI_{SD}/dt = 100A/µs (Note 4)	-	450	680	nC

NOTE:

2. Repetitive rating; pulse width limited by maximum junction temperature (See Figure 11)

Typical Performance Curves



FIGURE 1. OUTPUT CHARACTERISTICS



FIGURE 2. OUTPUT CHARACTERISTICS



FIGURE 3. TRANSFER CHARACTERISTICS



FIGURE 4. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE

Typical Performance Curves (Continued)



FIGURE 5. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



FIGURE 6. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT



FIGURE 7. SOURCE TO DRAIN DIODE FORWARD VOLTAGE



FIGURE 8. FORWARD BIAS SAFE OPERATING AREA



FIGURE 9. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE



FIGURE 10. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY

Typical Performance Curves (Continued)



FIGURE 11. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE

Test Circuits and Waveforms



FIGURE 12. UNCLAMPED ENERGY TEST CIRCUIT



FIGURE 13. UNCLAMPED ENERGY WAVEFORMS



FIGURE 14. GATE CHARGE TEST CIRCUIT



FIGURE 15. GATE CHARGE WAVEFORM

Test Circuits and Waveforms (Continued)



FIGURE 16. SWITCHING TIME TEST CIRCUIT



FIGURE 17. RESISTIVE SWITCHING WAVEFORMS

PSPICE Electrical Model

SUBCKT HRF3205P3 2 1 3 ; rev 7/25/97

CA 12 8 4.9e-9
CB 15 14 4.9e-9
CIN 6 8 3.45e-9

DBODY 7 5 DBODYMOD
DBREAK 5 11 DBREAKMOD
DPLCAP 10 5 DPLCAPMOD

EBREAK 11 7 17 18 57
EDS 14 8 5 8 1
EGS 13 8 6 8 1
ESG 6 10 6 8 1
EVTHRES 6 21 19 8 1
EVTEMP 20 6 18 22 1

IT 8 17 1

LDRAIN 2 5 1e-9
LGATE 1 9 2.6e-9
LSOURCE 3 7 1.1e-9
K1 LGATE LSOURCE 0.0085

MMED 16 6 8 8 MMEDMOD
MSTRO 16 6 8 8 MSTROMOD
MWEAK 16 21 8 8 MWEAKMOD

RBREAK 17 18 RBREAKMOD 1
RDRAIN 50 16 RDRAINMOD 3.5e-4
RGATE 9 20 0.36
RLDRAIN 2 5 10
RLGATE 1 9 26
RLSOURCE 3 7 11
RSLC1 5 51 RSLCMOD 1e-6
RSLC2 5 50 1e3
RSOURCE 8 7 RSOURCEMOD 4.5e-3
RVTHRES 22 8 RVTHRESMOD 1
RVTEMP 18 19 RVTEMPMOD 1

S1A 6 12 13 8 S1AMOD
S1B 13 12 13 8 S1BMOD
S2A 6 15 14 13 S2AMOD
S2B 13 15 14 13 S2BMOD

VBAT 22 19 DC 1



ESLC 51 50 VALUE={(V(5,51)/ABS(V(5,51)))*(PWR(V(5,51)/(1e-6*550),3))}

.MODEL DBODYMOD D (IS = 4.25e-12 RS = 1.8e-3 TRS1 = 2.75e-3 TRS2 = 5e-6 CJO = 5.95e-9 TT = 4e-7 M = 0.55)
.MODEL DBREAKMOD D (RS = 0.06 IKF = 30 TRS1 = -3e-3 TRS2 = 3e-6)
.MODEL DPLCAPMOD D (CJO = 4.45e-9 IS = 1e-30 N = 1 M = 0.88 VJ = 1.45)
.MODEL MMEDMOD NMOS (VTO = 2.93 KP = 9.5 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 1)
.MODEL MSTROMOD NMOS (VTO = 3.23 KP = 150 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u)
.MODEL MWEAKMOD NMOS (VTO = 2.35 KP = 0.02 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 10)
.MODEL RBREAKMOD RES (TC1 = 8e-4 TC2 = 4e-6)
.MODEL RDRAINMOD RES (TC1 = 8e-2 TC2 = 5e-6)
.MODEL RSLCMOD RES (TC1 = 1e-4 TC2 = 1.05e-6)
.MODEL RSOURCEMOD RES (TC1 = 1e-4 TC2 = 1.5e-5)
.MODEL RVTHRESMOD RES (TC1 = -2.3e-3 TC2 = -1.2e-5)
.MODEL RVTEMPMOD RES (TC1 = -2.2e-3 TC2 = -7e-6)

.MODEL S1AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -9 VOFF= -4)
.MODEL S1BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -4 VOFF= -9)
.MODEL S2AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = 0 VOFF= 2.5)
.MODEL S2BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = 2.5 VOFF= 0)

.ENDS

NOTE: For further discussion of the PSPICE model, consult **A New PSPICE Sub-Circuit for the Power MOSFET Featuring Global Temperature Options**; IEEE Power Electronics Specialist Conference Records, 1991, written by William J. Hepp and C. Frank Wheatley.

SPICE Thermal Model

REV 25 July 97

HRF3205

CTHERM1 7 6 2.53e-5
CTHERM2 6 5 1.38e-3
CTHERM3 5 4 7.00e-3
CTHERM4 4 3 2.50e-2
CTHERM5 3 2 1.33e-1
CTHERM6 2 1 5.75e-1

RTHERM1 7 6 7.78e-4
RTHERM2 6 5 8.55e-3
RTHERM3 5 4 3.00e-2
RTHERM4 4 3 1.42e-1
RTHERM5 3 2 2.65e-1
RTHERM6 2 1 2.33e-1



All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

Intersil semiconductor products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see web site **http://www.intersil.com**

Sales Office Headquarters

NORTH AMERICA
Intersil Corporation
P. O. Box 883, Mail Stop 53-204
Melbourne, FL 32902
TEL: (407) 724-7000
FAX: (407) 724-7240

EUROPE
Intersil SA
Mercure Center
100, Rue de la Fusee
1130 Brussels, Belgium
TEL: (32) 2.724.2111
FAX: (32) 2.724.22.05

ASIA
Intersil (Taiwan) Ltd.
7F-6, No. 101 Fu Hsing North Road
Taipei, Taiwan
Republic of China
TEL: (886) 2 2716 9310
FAX: (886) 2 2715 3029