



MATERIAL & FINISHES
 INSULATOR - PBT GLASS FILLED UL94V-0
 CONTACT - BRASS
 SHELL - STEEL
 PLATING - CONTACT
 - GOLD OVER NICKEL PLATED
 - SHELL
 NICKEL PLATED

ELECTRICAL CHARACTERISTICS
 RATING CURRENT : 3A
 CONTACT RESISTANCE : <15mΩ
 INSULATION RESISTANCE : >3000MΩ AT 500V
 DIELECTRIC VOLTAGE : 1000V AT 1 MINUTE
 OPERATING TEMPERATURE : -55° C TO+105° C

铆钉示意图

螺丝示意图

No. Of Contacts	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E
9	16.33	24.99	30.81	19.28	4.5
15	24.66	33.32	39.14	27.51	
25	38.38	47.04	53.04	41.30	
37	54.84	63.50	69.32	57.71	

TOLERANCE TABLE

.0	±0.30
.00	±0.15
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 Ckmtw CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LYF	2013-9-12	DMS-XP 母头 铆鱼叉锁螺丝

CLIENT P/N	/
UNIT	mm
SCALE	free
FILE NO.	Ckmtw-DMS-0004
REV.	A
	XH00