



Specifications:

规格:

Voltage rating:100V AC/DC
 额定电压: 100V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage:1000V AC/minute
 耐受电压: 1000V AC/分钟
 Temperature range:-40°C-+85°C
 温度范围: -40°C-+85°C
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max

K 205001 W V - XX - PT SN
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1.K-XKBTEK-Car Connector
- 2.XKB Series No
- 3.Categoiy:W-Wafer
- 4.Welding Board Angle:V-Straight 180°
- 5.Row No.Pin No:XX-02 Pin
- 6.Material:PT-PBT
- 7.Plating:SN-Tin Plating

K205001WV-XX-PTSN	PBT	Phosphor Bronze	K205001HM
PART NO	Material	Material(Pin)	Suitable XKB Housing

DSND		SCALE: N/A	MODEL TYPE: 2.0mm automotive connector
DWN		VIEW:	PART NO.: K205001WV-XX-PTSN
CHKD		UNIT: mm/in	DWG NO.: X-K205001WV-XX-PTSN
APPD		SIZE: A4	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGLAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5



XKB INDUSTRIAL PRECISION CO.,LIMITED