



Heavy-Duty C13 to C14 PDU-Style Power Extension Cable - 15A, 100–250V, 14 AWG, 6 ft., Blue Plugs

MODEL NUMBER: P005-006-BL









Computer power extension cord connects devices with C13/C14 power connectors or extends your existing power connection by 6 ft.

Features

C14-to-C13 Power Cable for Network Devices That Require a Heavy-Gauge Connection

This IEC-320-C14 to IEC-320-C13 cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C14 male to C13 female cord can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The six-foot length allows you flexibility in placing equipment with respect to the power outlet.

Color-Coded Connectors Avoid Misidentification That Can Cause Costly Downtime

This computer power extension cord features fully molded blue ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering computers, servers and other network devices
- 6 ft. length allows flexibility in placing devices in relationship to AC outlet
- PDU-style cord replaces or upgrades standard power cord provided by manufacturer
- Color-coded blue ends for fast, easy identification in a crowded rack or workstation
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU up to 6 ft. away in your data center
- Extend an existing power connection up to 6 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P005-006-BL Heavy-Duty C13 to C14 PDU-Style Power Extension Cable, 6 ft., Blue Plugs

Specifications



| OVERVIEW | |
|---------------------------------|------------------------------|
| UPC Code | 037332173225 |
| Country/Region | North America |
| INPUT | |
| Maximum Input Amps | 15 |
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.8 |
| Voltage Compatibility (VAC) | 100-250 |
| PHYSICAL | |
| Power Cord Jacket Type | SJT |
| Wire Gauge (AWG) | 14 |
| Wire Gauge (OD - mm²) | 2.08 |
| Shipping Dimensions (hwd / in.) | 0.25 x 5.80 x 8.80 |
| Shipping Dimensions (hwd / cm) | 0.64 x 14.73 x 22.35 |
| Shipping Weight (lbs.) | 0.70 |
| Shipping Weight (kg) | 0.32 |
| Color | Black; Blue |
| Number of Conductors | 3 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 F (-20 C) to 140 F (60 C) |
| Storage Temperature Range | -4 F (-20 C) to 140 F (60 C) |
| Operating Humidity Range | 10-85% RH |
| Storage Humidity Range | 10-85% RH |
| CONNECTIONS | |
| Side A - Connector 1 | IEC-320-C14 |
| Side B - Connector 1 | IEC-320-C13 |
| SPECIAL FEATURES | |
| High Voltage | Yes |
| Heavy-Duty | Yes |
| Locking Plug | No |
| WARRANTY | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|--|---------------------------|
|--|---------------------------|

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies