

## Snap-in markers - UCT-EM (7X10) - 0830765

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Snap-in markers, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped into marker carrier, lettering field size: 7 x 10 mm

### Your advantages

- ✓ UniCard snap-in device marking for Axioline E series.
- ✓ The markers, which are supplied in uniform sheets, can be marked quickly and easily using the BLUEMARK CLED and the THERMOMARK CARD.
- ✓ The wide temperature range means that the labels can be used in control cabinets as well as the field.



### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 10 pc   |
| GTIN         | <br>4 046356 745574 |
| GTIN         | 4046356745574   |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 10 mm |
| Width (a)  | 7 mm  |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
|---------------------------------|-------------------|

#### General

|  |  |
|--|--|
| Color                                  | white                                    |
| Components                             | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | V0                                       |
| Material                               | PC                                       |
| RoHS compliant                         | Yes                                      |
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1)              |
| Number of individual labels            | 30                                       |

# Snap-in markers - UCT-EM (7X10) - 0830765

## Technical data

### General

|   |                              |
|---|------------------------------|
| Number of individual labels per row                                 | 6                            |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02         |
| Result  | Test passed                  |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03 |
| Test duration   | 96 h                         |
| Result of weather resistance test                                   | Test passed                  |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02    |
| Test duration   | 96 h                         |
| Salt spray testing result   | Test passed                  |
| Wipe resistance of test specification inscriptions                  | IEC 61010-1:2010-06          |
| Result of wipe resistance test                                      | Test passed                  |
| Marking mounting type   | snapped into marker carrier  |
| Result  | Test passed                  |
| Oxygen index (DIN EN ISO 4589-2)                                    | 32.4 %                       |
| R22   | HL 1 - HL 3                  |
| R23   | HL 1 - HL 3                  |
| R24   | HL 1 - HL 3                  |

### Standards and Regulations

|  |                             |
|--|-----------------------------|
| Wipe resistance  | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94                 | V0                          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3                 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3                 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3                 |

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>