



## Product: 29503X

VFD 300% Gnd, 3C+IG #10 Str TC, XLPO Ins+PVC Grd, OS+TC Brd, Blk LSZH-TS Jkt, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable Marine Approved

[Request Sample](#)

### Product Description

Belden 300% Ground Flexible VFD, 3 Conductor 10AWG (105x30) Tinned Copper, XLPO Insulation M4 Color Code+PVC Insulated Ground, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, Black LSZH-TS Outer Jacket, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable Marine Approved SUN RES OIL RES II

### Technical Specifications

#### Product Overview

Suitable Applications:	AC Motor drives, VFD, Variable Frequency drives
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

Element	AWG	Stranding	Material	No. of Conductors
	10	105x30	TC - Tinned Copper	3
Ground Wire	10	105x30	TC - Tinned Copper	

Conductor Count:	3
------------------	---

##### Insulation

Material	Nominal Wall Thickness
XLPE - Cross Linked Polyethylene	0.045 in
XLP - Cross Linked Polyolefin	

##### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Duofoil®	100 %	TC - Tinned Copper	10	105x30 mm
Braid	2	TC - Tinned Copper		85 %			

##### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
Haloarrest Xlink 2	0.69 in	0.073 in

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR
0.988 Ohm/1000ft

##### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
29 pF/ft	53 pF/ft

##### Inductance

Nominal Inductance
0.184 µH/ft

##### Impedance

**Nominal Characteristic Impedance**

63 Ohm

**Current****Max. Recommended Current [A]**

40 Amps per conductor @ 30°C (per NEC)

**Voltage****UL Voltage Rating**

1000 V RMS (Flexible Motor Supply Cable)

600 V RMS (Type TC)

**Temperature Range**

UL Temp Rating: 90°C Dry, 90°C Wet

Wet Temp Range: -40°C To +90 °C

Dry Temp Range: -40°C To +90 °C

**Mechanical Characteristics**

Bulk Cable Weight: 350 lbs/1000ft

Max Recommended Pulling Tension: 592 lbs

Min Bend Radius/Minor Axis: 5.5 in

**Standards**

NEC/(UL) Specification: TC-ER, Unlisted Singles, WTTC

**Applicable Environmental and Other Programs**

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

CA Prop 65 (CJ for Wire &amp; Cable): Yes

MII Order #39 (China RoHS): Yes

**Suitability**

Suitability - Burial: Yes

Suitability - Indoor: Yes

Suitability - Oil Resistance: Yes

Suitability - Outdoor: Yes

Suitability - Sunlight Resistance: Yes

**Flammability, LSOH, Toxicity Testing**

UL Flammability: UL1685 UL Loading

CSA Flammability: FT4

IEEE Flammability: 1202

UL voltage rating: 1000 V RMS (Flexible Motor Supply Cable)

**Part Number****Variants**

Item #	Color	UPC	Length	Footnote
29503X 0105000	Black	612825137009	5,000 ft	C Z

Footnote: C - CRATE REEL PUT-UP.

Footnote: Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

**History**

Update and Revision: Revision Number: 0.212 Revision Date: 09-10-2019

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.