



SPECIFICATIONS:

1. CONDUCTOR:

- 1.1 CONDUCTORS: 24AWG $7 \times 0.19 \pm 0.015 \text{ mm}$
- 1.2 CONDUCTOR INSULATION COLOR CODING: ONE WHITE/ORANGE, ONE ORANGE, ONE WHITE/GREEN, ONE GREEN, ONE BLUE, ONE WHITE/BLUE, ONE WHITE/BROWN, ONE BROWN.

2. CABLE JACKET

- 2.1 PRINTING ON THE JACKET: CM (UL) C(UL) 4P 24AWG UTP CAT.5E PATCH CABLE

3. CABLE ASSEMBLY

- 3.1 SEE SECTION A-A FOR DIMENSIONS
- 3.2 CABLE TIE: WHITE TIE
- 3.3 WIRING T568B COLOR
- 3.4 CONTACT PLUG: RJ45 8P8C 3u pc UL 94V-2
- 4. CABLE JACKET COLOR: ACCORDING TO CUSTOMER'S REQUEST
- 5. Dielectric strength: 2.5KV dc-2seconds
- 6. Working temperatures: $-20 \sim 60^\circ \text{ c}$

DK-1511-XXX/XX

color:
BL(black), WH(white), B(blue), G(grey)

Length: (in feet)
1, 3, 5, 7, 10, 15, 20, 25, 50, 100

RoHS compliant

Scale	FREE					Date	Name	Customer-No.
TOLERANCE						Drawn	24.06.2014	Joanna
X.	$\pm X$					Approved	24.06.2014	Joanna
X.X								
X.XX								
DIM	TOL							
X.°								
		ⓐ	Drawn	24.06.2014	Joanna			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No. DK-1511-XXX/XX	
Drawing-No. ASS 7160 CA	rev00
Replace	SHEET