



- Technology Request:
- 1.Outlook:No burr, no hurt.
 - 2.Electronic performance:
 - a:Insulation resistance: Above DC500V/100MΩ;
 - b:Endure voltage:AC500V at 1 minute;
 - c>Contact resistance:Under 30mΩ;
 - 3.Insertion force & withdrawal force:0.3-3kgf.
 - 4.Salt spray test:24H.
 - 5.Meet RoHS.
 - 6.Remork * is important specificotion.

	MATERIAL	PLATING
PLASTIC	PBT	Black
termina 2	Brass	NI
termina 3	Brass	NI
termina 4	Phosphor Bronze	NI

					DSND		DATE		SCALE: N/A	DC POWER JACK			
ΔX					ANGLAR	±5°	DWN		VIEW:	PART NO.:			
ΔX					X.X	±0.2mm	CHKD		UNIT: mm/in	DWG NO.:			
ΔX					X.XX	±0.1mm	APPD		SIZE: A4	DC-351D-5A-1.35			
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm				WEIGHT	SHEET	REVISION	
REVISIONS					UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED			1.0g	1/1	A0
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn													