


Subminiature PCB Telecom Relay

PC312



FEATURES

- Subminiature design
- PC Terminals on .1 in. grid pattern
- Contact capacity from 1 mA to 5A
- Meets FCC part 68 voltage surge
- Class "B" insulation standard
- Three coil sensitivities available
- Sealed, immersion cleanable
- Lead Free & RoHS Compliant



File # E86876

UL/CSA RATINGS

Contact Form	1 Form C SPDT
Rated Load	3A @ 125VAC / 30 VDC
Rated Load (Special)	5A @ 120VAC / 30VDC
Max. Switching Current	3 Amps
Max. Switching Current (S)	5 Amps
Minimum Load (Gold Plated)	1 mA @ 1 VDC

CONTACT DATA

Material	Ag (Fine Silver), Ag+Au (Fine Silver Gold Clad) AgNi (Silver Nickel), AgCdO (Silver Cadmium Oxide)	
Initial Contact Resistance	100 milliohms max @ 0.1A, 6VDC (with Gold Plate)	
Service Life	Mechanical	1 X 10 ⁷ Operations
	Electrical	1 X 10 ⁵ Operations

CHARACTERISTICS

Operate Time	5 ms. Max.
Release Time	5 ms. Max.
Insulation Resistance	100 megohms min, at 500VDC, 50%RH
Dielectric Strength	1250 Vrms, 1 min. between coil and contacts 500 Vrms, 1 min. between open contacts: 750 Vrms, 1 min for S version
Surge Resistance	1500 V, between coil and contacts (FCC Part 68)
Shock Resistance	10 g, 11ms, functional; 100 g, destructive
Vibration Resistance	DA 1.5 mm, 10 - 55 Hz
Power Consumption	0.45 W, 0.36 W or 0.2 W
Ambient Temperature Range	-25 to 70 C operating, -30 to 130 storage
Weight	3.5 grams approx.

ORDERING INFORMATION

Example:	PC312	-12	H	S	-X
Model					
Coil Voltage					
Coil Sensitivity					
Nil: 0.36 W; B: 0.45 W; H: 0.2 W					
Current Rating					
Nil: Standard, 3 Amp; S: Special 5 Amp					
RoHS Compliant					
Nil: Not RoHS, -X: RoHS Compliant					

COIL DATA

Coil Voltage	Resistance ohms $\pm 10\%$			Must Operate Voltage Max. (VDC)	Must Release Voltage Min. (VDC)
	Sensitivity Code B 0.45 W	Standard Sensitivity 0.36 W	Sensitivity Code H 0.2 W		
3	20	25	45	2.25	0.3
5	56	70	120	3.75	0.5
6	80	100	180	4.50	0.6
9	180	220	440	6.75	0.9
12	320	400	700	9.00	1.2
18	720	900	1620	13.5	1.8
24	1280	1600	2800	18.00	2.4

Note: Custom coil voltages within the ranges shown are available on special order.

Dimensions in Inches (millimeters)




Drawings are 2X actual size

Side View

End View

Bottom View
PC Board Layout

Wiring Diagram



Notes:

Tolerances $\pm .010$ unless otherwise noted



3220 Commander Drive, Suite 102, Carrollton, Texas 75006

Sales: (888)997-3933 Fax: (818) 342-5296 email: sales@pickercomponents.com URL: pickercomponents.com