Designer's™ Data Sheet

Insulated Gate Bipolar Transistor

N–Channel Enhancement–Mode Silicon Gate


MGY25N120


Motorola Preferred Device

IGBT IN TO–264
25 A @ 90°C
38 A @ 25°C
1200 VOLTS
SHORT CIRCUIT RATED

This Insulated Gate Bipolar Transistor (IGBT) uses an advanced termination scheme to provide an enhanced and reliable high voltage blocking capability. Short circuit rated IGBT's are specifically suited for applications requiring a guaranteed short circuit withstand time. Fast switching characteristics result in efficient operation at high frequencies.

- Industry Standard High Power TO–264 Package (TO–3PBL)
- High Speed E_{off}: 216 μJ/A typical at 125°C
- High Short Circuit Capability – 10 μs minimum
- Robust High Voltage Termination





CASE 340G–02
STYLE 5
TO–264

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V_{CES}	1200	Vdc
Collector–Gate Voltage (R_{GE} = 1.0 MΩ)	V_{CGR}	1200	Vdc
Gate–Emitter Voltage — Continuous	V_{GE}	±20	Vdc
Collector Current — Continuous @ T_C = 25°C — Continuous @ T_C = 90°C — Repetitive Pulsed Current (1)	I_{C25} I_{C90} I_{CM}	38 25 76	Adc Apk
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	212 1.69	Watts W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–55 to 150	°C
Short Circuit Withstand Time (V_{CC} = 720 Vdc, V_{GE} = 15 Vdc, T_J = 125°C, R_G = 20 Ω)	t_{sc}	10	μs
Thermal Resistance — Junction to Case – IGBT — Junction to Ambient	$R_{\theta JC}$ $R_{\theta JA}$	0.6 35	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 5 seconds	T_L	260	°C
Mounting Torque, 6–32 or M3 screw	10 lbf•in (1.13 N•m)		

(1) Pulse width is limited by maximum junction temperature. Repetitive rating.

Designer's Data for "Worst Case" Conditions — The Designer's Data Sheet permits the design of most circuits entirely from the information presented. SOA Limit curves — representing boundaries on device characteristics — are given to facilitate "worst case" design.

Designer's is a trademark of Motorola, Inc.

Preferred devices are Motorola recommended choices for future use and best overall value.

REV 2

© Motorola, Inc. 1997

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector–to–Emitter Breakdown Voltage (V_{GE} = 0 Vdc, I_C = 25 μAdc)		$V_{(BR)CES}$	1200	—	—	Vdc
Temperature Coefficient (Positive)			—	960	—	mV/°C
Emitter–to–Collector Breakdown Voltage (V_{GE} = 0 Vdc, I_{EC} = 100 mAdc)		$V_{(BR)ECS}$	25	—	—	Vdc
Zero Gate Voltage Collector Current (V_{CE} = 1200 Vdc, V_{GE} = 0 Vdc)		I_{CES}	—	—	100	μAdc
(V_{CE} = 1200 Vdc, V_{GE} = 0 Vdc, T_J = 125°C)			—	—	2500	
Gate–Body Leakage Current (V_{GE} = ± 20 Vdc, V_{CE} = 0 Vdc)		I_{GES}	—	—	250	nAdc
ON CHARACTERISTICS (1)						
Collector–to–Emitter On–State Voltage (V_{GE} = 15 Vdc, I_C = 12.5 Adc)		$V_{CE(on)}$	—	2.37	3.24	Vdc
(V_{GE} = 15 Vdc, I_C = 12.5 Adc, T_J = 125°C)			—	2.15	—	
(V_{GE} = 15 Vdc, I_C = 25 Adc)			—	2.98	4.19	
Gate Threshold Voltage (V_{CE} = V_{GE}, I_C = 1.0 mAdc)		$V_{GE(th)}$	4.0	6.0	8.0	Vdc
Threshold Temperature Coefficient (Negative)			—	10	—	mV/°C
Forward Transconductance (V_{CE} = 10 Vdc, I_C = 25 Adc)		g_{fe}	—	12	—	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{CE} = 25 Vdc, V_{GE} = 0 Vdc, f = 1.0 MHz)	C_{ies}	—	2795	—	pF
Output Capacitance		C_{oes}	—	181	—	
Transfer Capacitance		C_{res}	—	45	—	
SWITCHING CHARACTERISTICS (1)						
Turn–On Delay Time	(V_{CC} = 720 Vdc, I_C = 25 Adc, V_{GE} = 15 Vdc, L = 300 μH, R_G = 20 Ω) Energy losses include “tail”	$t_{d(on)}$	—	91	—	ns
Rise Time		t_r	—	124	—	
Turn–Off Delay Time		$t_{d(off)}$	—	196	—	
Fall Time		t_f	—	310	—	
Turn–Off Switching Loss		E_{off}	—	2.44	4.69	mJ
Turn–On Delay Time	(V_{CC} = 720 Vdc, I_C = 25 Adc, V_{GE} = 15 Vdc, L = 300 μH, R_G = 20 Ω, T_J = 125°C) Energy losses include “tail”	$t_{d(on)}$	—	88	—	ns
Rise Time		t_r	—	126	—	
Turn–Off Delay Time		$t_{d(off)}$	—	236	—	
Fall Time		t_f	—	640	—	
Turn–Off Switching Loss		E_{off}	—	5.40	—	mJ
Gate Charge	(V_{CC} = 720 Vdc, I_C = 25 Adc, V_{GE} = 15 Vdc)	Q_T	—	97	—	nC
		Q_1	—	31	—	
		Q_2	—	40	—	
INTERNAL PACKAGE INDUCTANCE						
Internal Emitter Inductance (Measured from the emitter lead 0.25″ from package to emitter bond pad)		L_E	—	13	—	nH

(1) Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Transfer Characteristics




Figure 4. Collector–to–Emitter Saturation Voltage versus Junction Temperature




Figure 5. Capacitance Variation




Figure 6. Gate–to–Emitter Voltage versus Total Charge




Figure 7. Turn–Off Losses versus Gate Resistance




Figure 8. Turn–Off Losses versus Case Temperature




Figure 9. Reverse Biased Safe Operating Area





Figure 10. Thermal Response

PACKAGE DIMENSIONS



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	2.8	2.9	1.102	1.142
B	19.3	20.3	0.760	0.800
C	4.7	5.3	0.185	0.209
D	0.93	1.48	0.037	0.058
E	1.9	2.1	0.075	0.083
F	2.2	2.4	0.087	0.102
G	5.45 BSC		0.215 BSC	
H	2.6	3.0	0.102	0.118
J	0.43	0.78	0.017	0.031
K	17.6	18.8	0.693	0.740
L	11.0	11.4	0.433	0.449
N	3.95	4.75	0.156	0.187
P	2.2	2.6	0.087	0.102
Q	3.1	3.5	0.122	0.137
R	2.15	2.35	0.085	0.093
U	6.1	6.5	0.240	0.256
W	2.8	3.2	0.110	0.125

STYLE 5:
PIN 1. GATE
2. COLLECTOR
3. EMITTER

CASE 340G–02
TO–264
ISSUE F

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. “Typical” parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and Ⓜ are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

How to reach us:
USA / EUROPE / Locations Not Listed: Motorola Literature Distribution;
P.O. Box 5405, Denver, Colorado 80217. 1–303–675–2140 or 1–800–441–2447

JAPAN: Nippon Motorola Ltd.: SPD, Strategic Planning Office, 141,
4–32–1 Nishi–Gotanda, Shagawa–ku, Tokyo, Japan. 03–5487–8488

Customer Focus Center: 1–800–521–6274

Mfax™: RMFAX0@email.sps.mot.com – TOUCHTONE 1–602–244–6609
Motorola Fax Back System – US & Canada ONLY 1–800–774–1848
– http://sps.motorola.com/mfax/

ASIA / PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852–26629298

HOME PAGE: http://motorola.com/sps/