

SB10150FCT

SCHOTTKY BARRIER RECTIFIER

VOLTAGE: 150V

CURRENT: 10.0A




FEATURE

High current capability, Low forward voltage drop
Low power loss, high efficiency
High surge capability
High temperature soldering guaranteed
250°C /10sec/0.375" lead length at 5 lbs tension

MECHANICAL DATA

Terminal: Plated Insert leads, solderable per MIL-STD-750, Method 2026
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: Common Cathode
Mounting position: any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

| | SYMBOL | SB10150FCT | units |
|---|------------------------------------|-------------|-----------|
| Maximum Recurrent Peak Reverse Voltage | V _{rrm} | 150 | V |
| Maximum RMS Voltage | V _{rms} | 105 | V |
| Maximum DC blocking Voltage | V _{dc} | 150 | V |
| Maximum Average Forward Rectified Current | I _{f(av)} | 10 | A |
| Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load | I _{fsm} | 160 | A |
| Maximum Forward Voltage at 5A | V _f | 0.88 | V |
| Maximum DC Reverse Current at rated DC blocking voltage | I _r | 50 1.0 | μ A mA |
| Typical Thermal Resistance (Note 1) | R _{th(jc)} | 4.5 | °C/W |
| Operating Junction and Storage Temperature Range | T _j T _{stg} | -65 to +175 | °C |

Note:

1. Thermal Resistance from Junction to Case

Fig. 1 – Forward Derating Curve (Total)




Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Fig. 3 – Typical Instantaneous Forward Characteristics Per Leg




Fig. 4 – Typical Reverse Characteristics Per Leg




Fig. 6 – Typical Transient Thermal Impedance Per Leg

