


## 1. Features

1. Monolithic inorganic material construction.
2. Closed magnetic circuit avoids crosstalk.
3. Suitable for reflow soldering.
4. Shapes and dimensions follow E.I.A. spec.
5. Available in various sizes.
6. Excellent solder ability and heat resistance.
7. High reliability.
8. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
9. Low DC resistance structure of electrode to prevent wasteful electric power consumption.
10. Operating Temperature: -55~+125°C (Including self-temperature rise)



Certificate  
of  
Green Partner


## 2. Dimensions



Chip Size	
A	1.00±0.10
B	0.50±0.10
C	0.50±0.10
D	0.25±0.10

Units: mm

## 3. Part Numbering



- A: Series  
 B: Dimension  
 C: Material      Lead Free Material  
 D: Impedance    121=120Ω  
 E: Rated Current   20=2000mA  
 F: Category Code

## 4. Specification

Tai-Tech Part Number	Impedance (Ω)	Test Frequency (MHz)	DC Resistance (Ω) max.	Rated Current (mA) max.
MBP15K300-20A	30±25%	100	0.10	2000
MBP15K600-20A	60±25%	100	0.10	2000
MBP15K121-20A	120±25%	100	0.095	2000

- Rated current: based on temperature rise test
- In compliance with EIA 595

## Impedance Frequency Characteristics(Typical)

