* Representative image

Aluminum Compression Terminal for 336 - 350 AL/CU, 336.4 18/1 ACSR, 400 COMPACT

by ANDERSON
Catalog ID: VAUL35012

Aluminum Compression Terminal for 336 - 350 AL/CU, 336.4 18/1 ACSR, 400 COMPACT

- Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

Product Details

General

Crimp Method	VERSAtile™ (Accomodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	1
Plating	No
Style	Impact Extruded
UPC	096359334804

Dimensions

Diameter - Pad Bolt	0.5 in
Weight	0.196 lb

Conductor Related

Conductor Compatibility	ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAAC 6201 Alloy-Azusa-123.3-6/18;AAAC 6201 Alloy-Anaheim-155.4-6/18;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.684 in
Conductor Diameter (VersaCrimp) - Minimum	0.376 in

Certifications and Compliance

UL Listed	No

Logistics

Carton Quantity	80 EA

For further technical assistance, please contact us

Domestic Customer Service
Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service
Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com