

➔ Specifications

Parameter	Specification
Central Wavelength	980 nm, 1064 nm, 1310 nm, or 1550 nm
Bandwidth	± 20 nm
Attenuation Range	1-30 dB
Resolution	0.1 dB
PDL	0.1 dB (@ low attenuation)
Return Loss	50 dB
Fiber Type	SMF 28e or HI 1060 fiber
Power Handling	300 mW
Operating Temperature	0° C ~ + 70° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	15 mm x 13 mm x 6 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

M	V	O	A	-	3	0	-		-		-		
				Wavelength	Max Attenuation			Pigtail Length		Pigtail Style		Connector	
				0980: 980 nm	30: 30 dB			1: 1 meter		(=Package style)		0: None	7: LC/UPC
				1064: 1064 nm				2: 2 meter		B: bare fiber		1: FC/PC	8: LC/SPC
				1310: 1310 nm				S: Special		L: 900 μm loose tube		2: FC/APC	9: Special
				1550: 1550 nm						K: 2 mm cable		3: SC/PC	A: FC/UPC
										R: 3 mm cable		4: SC/APC	B: SC/UPC
												5: FC/SPC	C: ST
												6: SC/SPC	