



PCB LAYOUT

Specifications:

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating: 2A AC/DC  
 额定电流: 2A AC/DC  
 Withstanding voltage:1500V AC/minute  
 耐压电压: 1500V AC/分钟  
 Temperature range:-25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance: ≤20mΩ  
 接触电阻: ≤20mΩ  
 Linetype:AWG#22 AWG#24 AWG#26 AWG#28

X9254 W R X-XX X-N0 SN XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ①:Series No.
- ②:Category: W-WAFER
- ③:Welding Board Angle: R-Right Angle 90°
- ④:Welding Way: Blank-DIP
- ⑤:Row No.-Pin No.: XX-02P-30P
- ⑥:Plug the Pin & Special No.
- ⑦:Material: N0 -PA66 94V-0
- ⑧:Plating Category: SN-Bright Tin Plating
- ⑨:Color : Blank-Natural Color

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.08	10	22.86	25.40
3	5.08	7.62	11	25.40	27.94
4	7.62	10.16	12	27.94	30.48
5	10.16	12.70	13	30.48	33.02
6	12.70	15.24	14	33.02	35.56
7	15.24	17.78	15	35.56	73.66
8	17.78	20.32	30	73.66	76.20
9	20.32	22.86			

X9254WR-XX-N0SN	Nylon 66 UL 94V-0	Brass	Tin-Plated	X9254H
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	2.54mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO.,LIMITED			X9254WR-XX-N0SN
		WEIGHT	SHEET
		1.0g	1/1
		REVISION	A0

广东星坤科技股份有限公司

生	日期
發	
Δ	
文件工程章	

REVISIONS

DATE	REVISED	APPROVED

UNSPECIFIED TOLERANCES

www.xkb.cc.cn www.helloxkb.com www.helloxkb.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5