



SMA Female Precision Connector Solder Attachment 2 Hole
Flange Mount Solder Cup Terminal, .481 inch Hole Spacing

TECHNICAL DATA SHEET

PE44341

Configuration

Connector	SMA Female
Connector Interface Type	Solder Cup
Attachment Method (Shield/Contact)	Solder
Connector Design	Precision
Body Style	Straight
Mount Method	2 Hole Flange

Electrical Specifications

Frequency Range	DC to 27 GHz
Impedance	50 Ohms
Maximum VSWR	1.2:1
Maximum Insertion Loss	0.26 dB

Mechanical Specifications

Size

Length	0.575 in [14.61 mm]
Width/Dia.	0.223 in [5.66 mm]
Height	0.625 in [15.88 mm]
Weight	0.005 lbs [2.27 g]

Connector

Type	SMA Female
Contact Material and Plating	Beryllium Copper, Gold
Contact Plating Specification	MIL-G-45204, Type II, Class 1
Body Material and Plating	Stainless Steel, Gold
Body Plating Specification	MIL-G-45204
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)


RoHS Compliant	
REACH Compliant	06/18/2012

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female Precision Connector Solder Attachment 2 Hole Flange Mount Solder Cup Terminal, .481 inch Hole Spacing PE44341](#)

PE44341

PE44341 CAD Drawing

SMA Female Precision Connector Solder Attachment 2 Hole Flange
Mount Solder Cup Terminal, .481 inch Hole Spacing



- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. FITS MIL-C-17 AND EQUIVALENT CABLES.

DWG TITLE

PE44341

FSCM NO. 53919

2233

SIZE A

SCALE N/A

CAD FILE 092514

PE PASTERNAK
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com