

**NOTES:**

**MATERIAL**

1. Insulator Material: PBT+30%GF(UL94V-0)
2. Contact Material : Brass
3. Contact Plating :
  - AWP xx-7240-T : Gold flash over Ni
  - AWP xx-7540-T : Tin over Ni


**ELECTRICAL**

1. Current Rating : 3AMP
2. Withstand Voltage : 1000V AC/DC
3. Contact Resistance : 20mΩ max
4. Insulation Resistance: 1000MΩ min

**ENVIRONMENTAL**

1. Operation Temperature: -40°C to +105°C
2. Packing: Tray

- ④ 6P-8P Without Slot "M" and "N"
- 10P-12P With Slot "M" , Without Slot "N"
- 14P-64P With Slot "M" and "N"
- ⑥ Wire Spec: AWG28



Section A-A

**RoHS compliant**



File No.: E198287

⑤

| Scale     | Free  | ⑥   | Add wire spec      | 14.02.2014 | Amy    |          | Date       | Name | Customer-No.                            |
|-----------|-------|-----|--------------------|------------|--------|----------|------------|------|---|
| TOLERANCE |       | ⑤   | Add the UL-File No | 13.12.2013 | Winnie | Drawn    | 25.01.2006 | Alex | ASSMANN WSW-No.<br><b>AWP xx-7x40-T</b> |
| X.X       | ±0.40 | ④   | Update             | 27.03.2013 | Winnie | Approved | 14.02.2014 | Amy  |   |
| X.XX      | ±0.25 | ③   | New p/n added      | 21.12.2009 | Dean   |          |            |      |   |
| X.XXX     | ±0.15 | ②   | Redraw             | 13.03.2009 | Dean   |          |            |      | Drawing-No.                             |
| Angle     | ±3°   | ①   | Drawn              | 25.01.2006 | Alex   |          |            |      | <b>ASS 1194C CO</b> rev06               |
|           |       | Id. | Modification       | Date       | Name   |          |            |      | Replace                                 |
|           |       |     |                    |            |        |          |            |      |   |



**ASS 1194C CO** rev06

Replace

Sheet