



LED Lighting FSP25-FZAP(070)G

FEATURES

For LED Retail & Outdoor Application
Wide Input Range for Worldwide use (up to 305Vac)
Built-in PFC Function: up to PF 0.99
IP65 Design for Outdoor Installation
Suitable to Dry, Damp, Wet Location
High Surge Protection: 4kV(IEC61000-4-5)
High Reliability & Long Life 50,000hrs
Constant Current Design
Isolation Class II Design, No F.G.
Type HL LED Driver for use in Class I Division 2 hazardous location luminaires
All-Round Protections: Short Circuit/ Over Voltage/ Over Temperature
Safety: Meet IEC61347-2-13, UL8750 & EMI EN55015



PRODUCT HIGHLIGHT

Output Voltage/Current 700mA/22-37V

:

SPECIFICATION

Model Name	FSP25-FZAP(070)G	
Wattage	25W	
Case	Plastic	
IP Level	IP65	
Input Electrical Specification	Input Voltage	100~277 Vac
	Input Frequency	47~63 Hz
	PFC	≥ 0.99
	Input Current	≤ 0.3A /120Vac ; ≤ 0.2A /230Vac ; ≤ 0.2A /277Vac
	Inrush Current	5A
Constant Current / Constant Voltage	Constant Current	
Output Voltage and Current Rating	Output1	22-37 V , 700 mA
Output Electrical Specification	Efficiency	≥ 88 %
	Life	50,000 hours at Tcase of ≤ 70°C
	Protection Function	OVP,OTP,OPP,SCP
Environmental Requirement	TEMP. Range	Operating : -25°C to +70°C Storage : -35°C to +70°C
EMC performance	EN55015	Class B Conducted, Class B radiated
	EN61000-3-2	Class C
	EN61000-4-5	Differential Mode: 4KV
Dimension	78mm(L) x 80.3mm(W)x 25.4mm(H)	

PROTECTION FUNCTIONS

OVP,OTP,OPP,SCP

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice