



## Main

|                       |                                      |
|-----------------------|--------------------------------------|
| Product               | Miniature circuit-breaker            |
| Range                 | QO                                   |
| Current Rating        | 100 A                                |
| Voltage Rating        | 120/240 V AC<br>240 V AC<br>120 V AC |
| Mounting Type         | Bolt-on                              |
| Number of Poles       | 2P                                   |
| Circuit Breaker Type  | Standard                             |
| Ratings               | HACR rated                           |
| Electrical Connection | Box lugs                             |

## Complementary

|                        |  |
|------------------------|--|
| Interrupt Rating       | 22 kA 120/240 V AC 50/60 Hz<br>22 kA 240 V AC 50/60 Hz<br>22 kA 120 V AC 50/60 Hz          |
| Number of Panel Spaces | 2  |
| Wire Size              | AWG 4...AWG 2/0 copper or aluminium  |
| Tightening torque      | 44.25 lbf.in (5 N.m) 0.02...0.04 in <sup>2</sup> (10...25 mm <sup>2</sup> ) AWG 8...AWG 2) |
| Height                 | 88.90 mm (3.5 in)  |
| Depth                  | 73.91 mm (2.91 in)   |
| Width                  | 38.10 mm (1.5 in)  |

## Environment

|                |                  |
|----------------|------------------|
| Certifications | UL listed<br>CSA |
| Ambient Rating | 122 °F (50 °C)   |

Ordering and shipping details

---

|                     |                      |
|---------------------|----------------------|
| Package weight(Lbs) | 12.00 oz (340.194 g) |
|---------------------|----------------------|

---

Offer Sustainability

---

|                   |                     |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|

---