



规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触电阻: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area
Tin On Solder Talls
2. 外壳: Shell:
铜壳四周镀80U”(MIN)镍
端子四周镀50U”(MIN)锡, 镀金区域镀100-200U”镀金1U”

Nickel Plating

成品图 MANUFACTURE DWG		深圳市金航标电子有限公司				WWW.BDS666.COM	
公差一览表 TOLERANCE UNLESS OTHERWISE		KH-AF180ZJ-17.5				0755-83044319	
.X±0.15	.X±5°	日期 DATE	单位 UNIT	MM	制图 DRAWING	DWG NO.	DWGNO.
.XX±0.05	.X±2°	审核 CHECKED	比例 SCALE	1:1	设计 DESIGN	品名 NAME	规格 SPECIFICATION
.XXX±0.02	.XX±1°	核准 APPROVE	画法 VIEW	第一角 第一角		版本 VER	页数 SHEET