






RoHS



NOTE:  
 1.Rating: 24V 25mA DC  
 2.Insulation Resistance: ≥100 MΩ  
 3.Withstand voltage: AC 500V 1Minute  
 4.Operating Force Range: 400gf Max  
 5.Mechanical Life: 3,000 Cycles

Number of digits(位数)	1P	2P	3P	4P	5P	6P	7P	8P	9P	10P	12P
Cover/red 盖子/红色	凸柄 Convex handle TE-01	TE-02	TE-03	TE-04	TE-05	TE-06	TE-07	TE-08	TE-09	TE-10	TE-12
	短柄 Short handle TE-01D	TE-02D	TE-03D	TE-04D	TE-05D	TE-06D	TE-07D	TE-08D	TE-09D	TE-10D	TE-12D
Cover/blue 盖子/蓝色	凸柄 Convex handle TE-01R	TE-02R	TE-03R	TE-04R	TE-05R	TE-06R	TE-07R	TE-08R	TE-09R	TE-10R	TE-12R
	短柄 Short handle TE-01L	TE-02L	TE-03L	TE-04L	TE-05L	TE-06L	TE-07L	TE-08L	TE-09L	TE-10L	TE-12L

Ⓔ	Terminal		4	Phosphorus bronze	Gold plating
Ⓓ	Potting glue			Epoxy resin	Black
Ⓒ	Handle		2	PBT	White
Ⓑ	Cover		1	PBT	Red/Blue
Ⓐ	Base		1	PBT	Black
NO.	Name	Number	Qty	Materil	Remarks

YUANDI® Yuandi Electronics Co, Ltd  
元迪

design	date	name	DIP SWITCH
Review	date	model	TE-02R
Approved	date		

Drawing number:      angle      ±2'      10~30      ±0.30      5~10      ±0.20      ~ 5      ±0.10      Tolerance not specified      Proportion      1:1      unit      mm      gage number      A4

modify      Review      Approved