




Surface Mount, Phase Control SCR 0.8 Amperes/400-600 Volts

OUTLINE DRAWING



CONNECTION DIAGRAM

① CATHODE
② ANODE
③ GATE



Description:

The Powerex CR08AS Phase Control SCRs are glass passivated thyristors for use in low power control and rectification. These devices are molded epoxy plastic types.

Features:

- ☐ Surface Mount Type
- ☐ Glass Passivated
- ☐ Gate Trigger Current is Small
- ☐ Easy Application for Printed Circuits

Applications:

- ☐ Solid State Relay
- ☐ Static Switches
- ☐ Ignitors
- ☐ Strobe Flasher

Ordering Information:

Example: Select the complete seven or eight digit part number you desire from the table - i.e. CR08AS-8 is a 400 Volt, 0.8 Ampere Phase Control SCR.

Outline Drawing (Conforms to SOT-89)

Dimensions	Inches	Millimeters
A	0.18 Max.	4.6 Max.
B	0.17 Max.	4.2 Max.
C	0.12	3.0
D	0.10 ± 0.004	2.5 ± 0.1
E	0.06 ± 0.008	1.6 ± 0.2
F	0.06 ± 0.004	1.5 ± 0.1

Dimensions	Inches	Millimeters
G	0.06	1.5
H	0.031 Min.	0.8 Min.
J	0.021 Max.	0.58 Max.
K	0.019 Max.	0.48 Max.
L	0.016+0.001/-0.002	0.4+0.03/-0.05

Type	V _{DRM} /V _{RRM} Volts	Code
CR08AS	400	-8
	600	-12



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

CR08AS

Surface Mount, Phase Control SCR

0.8 Amperes/400-600 Volts

Absolute Maximum Ratings, $T_a = 25\text{ }^{\circ}\text{C}$ unless otherwise specified

Ratings	Symbol	CR08AS-8 (Marked "AD")	CR08AS-12 (Marked "AF")	Units
Repetitive Peak Off-state Voltage	V_{DRM}	400	600	Volts
Repetitive Peak Reverse Voltage	V_{RRM}	400	600	Volts
Non-repetitive Peak Reverse Voltage	V_{RSM}	500	720	Volts
DC Reverse Voltage	$V_{\text{R(DC)}}$	320	480	Volts
DC Forward Voltage	$V_{\text{D(DC)}}$	320	480	Volts
RMS On-state Current	$I_{\text{T(RMS)}}$	1.26	1.26	Amperes
Average On-state Current (Nominal, See Graphs) $T_a = 51\text{ }^{\circ}\text{C}$	$I_{\text{T(avg)}}$	0.8	0.8	Amperes
Non-repetitive Peak Surge, On-state Current One Cycle (60 Hz)	I_{TSM}	10	10	Amperes
I^2t for Fusing, $t = 8.3\text{ msec}$	I^2t	0.42	0.42	A^2sec
Peak Gate Power Dissipation	P_{GM}	0.5	0.5	Watts
Average Gate Power Dissipation	$P_{\text{G(avg)}}$	0.1	0.1	Watts
Peak Forward Gate Current	I_{FGM}	0.3	0.3	Amperes
Peak Forward Gate Voltage	V_{FGM}	6	6	Volts
Peak Reverse Gate Voltage	V_{RGM}	6	6	Volts
Storage Temperature	T_{stg}	-40 to 125	-40 to 125	$^{\circ}\text{C}$
Operating Junction Temperature	T_{j}	-40 to 125	-40 to 125	$^{\circ}\text{C}$
Weight	—	48	48	mg

CR08AS

Surface Mount, Phase Control SCR

0.8 Amperes/400-600 Volts


Electrical and Thermal Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Voltage – Blocking State						
Peak Forward Leakage	I_{DRM}	$T_j = 125^\circ\text{C}$, $V_D = V_{\text{DRM}}$	–	–	0.5	mA
Peak Reverse Leakage	I_{RRM}	$T_j = 125^\circ\text{C}$, $V_R = V_{\text{RRM}}$	–	–	0.5	mA
Current – Conducting State						
Peak On-state Voltage	V_{TM}	$T_c = 25^\circ\text{C}$, $I_{\text{TM}} = 2.5\text{A}$	–	–	1.5	Volts
DC Holding Current	I_{H}	$V_D = 12\text{V}$, $R_{\text{GK}} = 1\text{k}\Omega$, $T_j = 25^\circ\text{C}$	–	1.5	3.0	mA
Thermal Resistance, Junction-to-ambient	$R_{\text{th(j-a)}}$	–	–	–	65	$^\circ\text{C/Watt}$
Gate – Parameters						
Gate Current to Trigger [†] *	I_{GT}	$V_D = 6\text{V}$, $R_L = 60\Omega$, $T_j = 25^\circ\text{C}$	–	–	100	μA
Gate Voltage to Trigger [†]	V_{GT}	$V_D = 6\text{V}$, $R_L = 60\Omega$, $T_j = 25^\circ\text{C}$	–	–	0.8	Volts
Non-triggering Gate Voltage	V_{GD}	$V_D = 1/2V_{\text{DRM}}$, $R_{\text{GK}} = 1\text{k}\Omega$, $T_j = 125^\circ\text{C}$	0.3	–	–	Volts

[†] I_{GT} , V_{GT} Measurement Circuit

* If special values of I_{GT} are required, choose at least two items from those listed in the table below; i.e. A-B or B-C.

Item	A	B	C
$I_{\text{GT}} (\mu\text{A})$	1-30	20-50	40-100





CR08AS


Surface Mount, Phase Control SCR

0.8 Amperes/400-600 Volts


MAXIMUM ON-STATE CHARACTERISTICS




GATE CHARACTERISTICS




MAXIMUM SURGE CURRENT FOLLOWING RATED LOAD CONDITIONS




ALLOWABLE AMBIENT TEMPERATURE VS. AVERAGE ON-STATE CURRENT (SINGLE-PHASE HALF WAVEFORM)




ALLOWABLE AMBIENT TEMPERATURE VS. AVERAGE ON-STATE CURRENT (SINGLE-PHASE HALF WAVEFORM)




MAXIMUM ON-STATE POWER DISSIPATION (SINGLE-PHASE HALF WAVEFORM)



ALLOWABLE AMBIENT TEMPERATURE VS. AVERAGE ON-STATE CURRENT (SINGLE-PHASE FULL WAVEFORM)












MAXIMUM ON-STATE POWER DISSIPATION (SINGLE-PHASE FULL WAVEFORM)



CR08AS

Surface Mount, Phase Control SCR
0.8 Amperes/400-600 Volts



CR08AS

Surface Mount, Phase Control SCR

0.8 Amperes/400-600 Volts

