


1. Rated load: 30V 2.5A
1. 额定负载: 30V 2.5A
2. Contact Resistance: $\leq 0.03\Omega$;
2. 接触电阻: $\leq 0.03\Omega$;
3. Insulation Resistance: $\geq 100M\Omega$;
3. 绝缘电阻: $\geq 100M\Omega$;
4. Voltage withstand: AC500V(50Hz)/min;
4. 耐压: AC500V (50Hz) /min;
5. Insertion force: 3~20N;
5. 插入力: 3~20N;
- life: 5,000次.
6. 寿命: 5000次.


SCHEMATIC	
Model	DC-005F-2.5A
Center Pin	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
center pin	Brass	CuSn
terminal 1	Brass	Ag
terminal 2	Phosphor copper	Ag
terminal 3	Brass	Ag
plastic	Pbt	

广东星坤科技股份有限公司

生效日期									
文件工程章	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED				

ANGLAR	±5°
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm
UNSPECIFIED TOLERANCES	

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK	
DWN		DATE		VIEW: 	PART NO.:	
CHKD		DATE		UNIT: mm/in	DWG NO.:	
APPD		DATE		SIZE: A4	DC-005F-2.5A-2.0	
XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0