


Sales Region	Worldwide (except Japan)
Series	GENESYS+
Model	G+Rack 60kW
Status	 Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to here.



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	170 to 265Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	150Vdc
Output Voltage[DC]	0 to 150Vdc
Rated Output Current	408A
Output Current	0 to 408A
Rated Output Power	61.2kW
Efficiency	90% Typ.
Voltage Ripple Noise	
Current Ripple Noise	

Package Type & Size

Package Type	Rack DC System
Width(W)	553mm Nom. (21.77in Nom.)
Height(H)	1028mm Nom. (40.47in Nom.)
Depth(D)	902mm Nom. (35.51in Nom.)
Weight	200kg Typ. (440.9lbs Typ.)

Other

Interfaces Included	LAN (LXI compliant)
	USB
	RS-232
	RS-485
Interface Options	Isolated analog voltage control
	GPIB
	EtherCAT
Operating Temp. Range	Modbus-TCP
	0 to 50°C

Safety Standard(Certified)	IEC61010-1 EN61010-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.