

ZWD100PAF-0524/JA



Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak power capability
Option	JST connector type With cover type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	81% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>4A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	100W
Total Maximum Peak Power	196W

Cases Shape & Size

Case'□' shape	PC board
Width(W)	85mm Nom.
Height(H)	46mm Nom.
Depth(D)	252mm Nom.
Weight	780g Typ.

Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1 EN50178
Safety Standard(Conformed)	Den-an

