
PETERMANN-TECHNIK GmbH
Lechwiesenstr. 13
D-86899 Landsberg am Lech
Fon: +49/8191/305395
Fax: +49/8191/305397
www.petermann-technik.com
info@petermann-technik.com



SMD WATCH CRYSTAL SERIES M3215

FEATURES

- Smallest available low cost watch crystal
- Ultra low profile
- Standard operating temperature range of -40/+85°C
- Excellent clock signal generatur for CPU´s


Pb free
RoHS-2 2011/65/EU
compliant

GENERAL DATA

SMD-CRYSTAL SERIES	M3215 (3.2x1.5x0.85mm)
NUMBER OF SOLDER PADS	2
FREQUENCY RANGE	32.768 kHz
FREQUENCY TOLERANCES AT 25°C	±20 ppm (standard) / ±10 ~ ±100 ppm (option)
LOAD CAPACITANCE (C_L)	12.5 pF (standard) 6,7,9 and 10pF available on request
WORKING TEMPERATURE RANGES	-40/+85°C
RESONANCE RESISTANCE	80 kΩ max.
SHUNT CAPACITANCE C0	1.3 pF typ.
TURNOVER TEMPERATURE	+25°C +-5°C
PARABOLIC COEFFICIENT	-0.04 ppm/°C²
DRIVE LEVEL	0.2 µW typical (1.0 µW max.)
AGING	±3 ppm max. per year
INSULATION RESISTANCE	>500 MΩ DC/100V ±10%
STORAGE TEMPERATURE	-55°/+125°C
DELIVERY FORM	Tape and Reel (1.000 ~ 3.000 pcs per reel)

OTHER PARAMETERS ARE AVAILABLE ON REQUEST / CREATE HERE YOUR SPECIFICATION

DIMENSIONS



Unit: mm

CRYSTALS
OSCILLATORS
CERAMIC RESONATORS

Premium Quality by PETERMANN-TECHNIK

CERAMIC FILTERS
SAW COMPONENTS

PETERMANN-TECHNIK GmbH
Lechwiesenstr. 13
D-86899 Landsberg am Lech
Fon: +49/8191/305395
Fax: +49/8191/305397
www.petermann-technik.com
info@petermann-technik.com

ORDERING INFORMATION

Series	Frequency	Frequency Stability at 25°C	Temperature Range	Load Capacitance
M3215	32.768 kHz	20	-40+85°C	12.5 pF