

Software - DIAG+ NETSCAN CPY - 2868088

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The Diag+ NetScan copy license enables the installation and parallel use of the Diag+ NetScan software on multiple workstations. It is a workstation license. A workstation full license is also required.



DIAG+ NETSCAN
Automatic INTERBUS Diagnostics



Key Commercial Data

Packing unit	1 STK
Custom tariff number	49119900
Country of origin	Germany

Technical data

License information

Type of software	Configuration
	Diagnostics
	Data acquisition
	Communication
	Startup
	Servicing
	DIN EN 61131-3 compliant
	Security

Functions

Number of I/O nodes	not relevant
Basic functions	Executing important commands (start/stop/...)
	Reading in the installed bus structure
	Detecting/representing error states (plain text from knowledge database)
	Saving diagnostics data in flash memory or parameterizing memory of the controller board

Software - DIAG+ NETSCAN CPY - 2868088

Technical data

Functions

	Diagnostics of FO paths (transmission quality)
	Can be integrated into other 32-bit applications as ActiveX Control
Expanded functionality	Cyclical readout of diagnostic data from all INTERBUS controller boards/controllers in the network overview (the number of controller boards is not limited)
	Network overview: All INTERBUS controller boards/controllers in a system are clearly shown in a tree view; detailed diagnostics can be called up by clicking on the corresponding item
	Monitoring function: Simultaneous monitoring of up to 10 INTERBUS controller boards/controllers maximum
Supported controllers	INTERBUS Generation 4 controller board
Configuration	INTERBUS, PROFINET
Diagnostics	INTERBUS, PROFINET

Hardware requirements

Hard disk	min. 2 GByte
CPU	min. Intel® Pentium® 4 / Celeron® 1,6 GHz
Interfaces	Serial interface, Ethernet, PCI
Optical drive	DVD-ROM
Monitor resolution	XGA (1024 x 768)
Operating equipment	Keyboard, mouse

Software requirements

Operating systems	Windows® 7 Professional SP1 (32-Bit/64-Bit)
	Windows® 7 Ultimate SP1 (32-Bit/64-Bit)
	Windows® 8.1 Professional (32-Bit/64-Bit)
	Windows® 8.1 Enterprise (32-Bit/64-Bit)
	Windows® 10 (32-bit/64-bit), as of Build 1511
Languages supported	German, English, French, Italian, Spanish, Chinese
Supported browsers	Internet Explorer Version 8 or later

Classifications

eCl@ss

eCl@ss 4.0	27250270
eCl@ss 4.1	27250270
eCl@ss 5.0	27242501
eCl@ss 5.1	27242501
eCl@ss 6.0	27242501

Software - DIAG+ NETSCAN CPY - 2868088

Classifications

eCl@ss

eCl@ss 7.0	27242501
eCl@ss 8.0	27242501
eCl@ss 9.0	27242501

ETIM

ETIM 2.0	EC001435
ETIM 3.0	EC001435
ETIM 4.0	EC000809
ETIM 5.0	EC000809

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43232401
UNSPSC 13.2	43232401