Mallory Sonalert Products,Inc.

Part #:	ZA028LDMT8
Revision:	F

Sales Outline Drawing

Specifications:

Sound Level Category:	Loud	Loud	Loud	Loud
Mode of Operation:	Continuous	Fast Pulse @ 10 PPS	Chime @ Once per 3 Seconds	Dual Tone 3.8 - 3.7 kHz @ 1.5 WPS
Loudness @ 2 FT:	85 to 95 dB(A) Typ.	85 to 95 dB(A) Typ.	85 to 95 dB(A) Typ.	85 to 95 dB(A) Typ.
Frequency:	3900 ± 500 Hz	3900 ± 500 Hz	3700 ± 500 Hz	3700 ± 500 Hz
Connection:	"+" to Positive, "-" to Ground	"+" to Positive, "-" and "1" to Ground	"+" to Positive, "-" and "2" to Ground	"+" to Positive, "-", "1" and "2" to Ground


Voltage Rating:	16 to 28 VDC
Current Draw:	40mA MAX
Housing Material:	6/6 Nylon, Color: Black
Storage Temperature:	-40° to +80° C
Operating Temperature	-30° to +65° C
Panel Mounting:	Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole.
Knurled Nut:	Used to attach part to panel. The max recommended torque is 10 in-lbs.
Weight (Typical):	28 g
NEMA 3R,4X, & 12:	Approved with use of included gasket.
cUL Recognition	cUL Recognized
Options:	Please contact factory.


Dimensions: Inches (mm)

cUL Recognized

PATENT NUMBER 9576442

ROHS Compliant





4411 South High School Road, Indianapolis, Indiana 46241 U.S.A · Phone: (317) 612-1000 Fax: (317) 612-1010 www.mallory-sonalert.com