StaticGuard

AVX Multilayer Ceramic Transient Voltage Suppressors
ESD Protection for CMOS, Bi Polar and SiGe Based Systems

GENERAL INFORMATION

- Typical ESD failure voltage for CMOS and/or Bi Polar is ≥ 200V.
- 15kV ESD pulse (air discharge) per IEC 1000-4-2, Level 4, generates < 20 millijoules of energy.
- Low capacitance (<200pF) is required for high-speed data transmission.
- Low leakage current (I_L) is necessary for battery operated equipment.

StaticGuard

AVX Part Number	Working Voltage (DC)	Working Voltage (AC)	Clamping Voltage	Test Current For V_c	Maximum Leakage Current	Transient Energy Rating	Peak Current Rating	Typical Cap	Case Size	Elements
VC04LC18V500 _ _	≤18.0	≤14.0	50	1	10	0.02	15	40	0402	1
VC06LC18X500 _ _	≤18.0	≤14.0	50	1	10	0.05	30	50	0603	1
VC08LC18A500 _ _	≤18.0	≤14.0	50	1	10	0.10	30	80	0805	1
VC12LC18A500 _ _	≤18.0	≤14.0	50	1	10	0.10	30	200	1206	1
VA10LC18A500 _ _	≤18.0	≤14.0	50	1	10	0.10	30	200	Axial	1

└ Termination/Lead Finish Code
└ Packaging Code

V_W(DC)	DC Working Voltage (V)
V_W(AC)	AC Working Voltage (V)
V_C	Clamping Voltage (V @ I_{VC})
I_{VC}	Test Current for V_C (A, 8x20µS)
I_L	Maximum Leakage Current at the Working Voltage (µA)
E_T	Transient Energy Rating (J, 10x1000µS)
I_P	Peak Current Rating (A, 8x20µS)
Cap	Typical Capacitance (pF) @ frequency specified and 0.5 V

Not RoHS Compliant

LEAD-FREE
LEAD-FREE COMPATIBLE COMPONENT

RoHS COMPLIANT

For RoHS compliant products, please select correct termination style.

PART NUMBER IDENTIFICATION

Chips

V C 08 LC 18 A 500 R P

- **TERMINATION FINISH:** P = Ni/Sn Alloy (Plated)
- **PACKAGING (Pcs/Reel)**
- **CLAMPING VOLTAGE**
- **ENERGY RATING**
- **WORKING VOLTAGE (0-18VDC)**
- **LOW CAPACITANCE DESIGN**
- **CASE SIZE DESIGNATOR**
- **CASE STYLE**
- **PRODUCT DESIGNATOR**


Axials

V A 10 LC 18 A 500 R L


- **LEAD FINISH:** L = Copper Clad Steel, Solder Coated
- **PACKAGING (Pcs/Reel)**
- **CLAMPING VOLTAGE**
- **ENERGY RATING**
- **WORKING VOLTAGE (0-18VDC)**
- **LOW CAPACITANCE DESIGN**
- **CASE SIZE DESIGNATOR**
- **CASE STYLE**
- **PRODUCT DESIGNATOR**

TYPICAL PERFORMANCE DATA


VC06LC18X500 Capacitance Histogram




StaticGuard ESD RESPONSE
IEC 1000-4-2 (8 Kv Contact Discharge)




VC08LC18A500 Capacitance Histogram




StaticGuard S21



VC12LC18A500 Capacitance Histogram




VI Curves - StaticGuard Products



TYPICAL PERFORMANCE CURVES (0402 CHIP SIZE)

VOLTAGE/CURRENT CHARACTERISTICS


Multilayer construction and improved grain structure result in excellent transient clamping characteristics up to 20 amps peak current, while maintaining very low leakage currents under DC operating conditions. The VI curves below show the voltage/current characteristics for the 5.6V, 9V, 14V, 18V and low capacitance StaticGuard parts with currents ranging from parts of a micro amp to tens of amps.




PULSE DEGRADATION

Traditionally varistors have suffered degradation of electrical performance with repeated high current pulses resulting in decreased breakdown voltage and increased leakage current. It has been suggested that irregular intergranular boundaries and bulk material result in restricted current paths and other non-Schottky barrier paralleled conduction paths in the ceramic. Repeated pulsing of TransGuard® transient voltage suppressors with 150Amp peak 8 x 20µS waveforms shows negligible degradation in breakdown voltage and minimal increases in leakage current. This does not mean that TransGuard® suppressors do not suffer degradation, but it occurs at much higher current.

ESD TEST OF 0402 PARTS



PEAK POWER VS PULSE DURATION



INSERTION LOSS CHARACTERISTICS

