



Sales Region	Worldwide
Series	CCG
Status	Production
Option	Positive logic ON/OFF control
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Rated Input Voltage[DC]	12/24V
Input Voltage Range[DC]	9 to 36V
Efficiency	89% Typ.
Rated Output Voltage[DC]	5V
Output Voltage Range[DC]	4.5 to 5.5V
Maximum Output Current	
Maximum Ripple Noise	70mV
Maximum Output Power	30W
Withstanding Voltage1	Input - Case: 1000VDC: 1min.
Withstanding Voltage2	Input - Output: 1500VDC: 1min.
Withstanding Voltage3	Output - Case: 1000VDC: 1min.

Cases Shape & Size

Case'□' shape	On board/Power module
Width(W)	25.4mm Nom.
Height(H)	9.9mm Nom.
Depth(D)	25.4mm Nom.
Weight	20g Typ.
Industry Standard Size	1x1 inch size
Terminal Style	DIP

Other

Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	

