

MATERIAL:

Body: Nylon66, UL rated:94V-2 min

Actuator: Nylon66, UL rated:94V-2 min

Terminal: Brass, silver plated

Rating: 40A 125V AC

25A 250V AC

Function: ON-OFF

Protection Grade: IP65

Contact Resistance: 50mΩ Max



Insulation Resistance: 100MΩ Min at DC 500V

Dielectric Strength: 2000V/AC 1 minute



Electrical life: 10,000 cycles




Mechanical life :50,000 cycles

Operating Temperature: -20℃~80℃

Safety Approval:   

CUT-OUT



SWITCHING CIRCUIT	X	Y
	30.0+0.1	22.0+0.1
	30.2+0.1	22.0+0.1
	30.4+0.1	22.0+0.1



公差 TOLERANCES .X±0.3 .XX±0.15 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	版本 VERSION	核准 APPROVED BY	比例尺 SCALE	核对 CHECKED BY	日期 DATE	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				A0		1:1		2021.09.29	孙成	R-6-210-W5L-BR	1040070