ROITHNER LASERTECHNIK GmbH
WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
TEL. +43 1 586 52 43 -0, FAX. -44 OFFICE@ROITHNER-LASER.COM

rev 2.0 07.06.2016

LED545-01

- Green LED
- 545 nm, 2 mW
- Chip Material: InGaN
- 5 mm Clear Mold, Epoxy Resin
- Viewing Angle: 16°

Description

LED545-01 contains a InGaN LED mounted on a lead frame hermetically sealed with a clear epoxy lens. On forward bias, it emits a power radiation of typical **2 mW** at a peak wavelength at **545 nm**.

Maximum Ratings (T_{CASE}=25°C)

Parameter	Symbol	Values Min.	Values Max.	Unit
Power Dissipation	P_D		180	mW
Forward Current	I_F		50	mA
Pulse Forward Current *1	I_{FP}		100	mA
Reverse Voltage	V_F		5	V
Thermal Resistance	R_{THJA}		330	K/W
Junction Temperature	T_J		100	°C
Operating Temperature	T_{CASE}	- 40	+ 85	°C
Storage Temperature	T_{STG}	- 40	+ 100	°C
Lead Solder Temperature *2	T_{SLD}		+ 265	°C

*1 *duty=1%, pulse width = 10 µs*
*2 *must be completed within 3 seconds*

Electro-Optical Characteristics (T_{CASE}=25°C)

Parameter	Symbol	Conditions	Values Min.	Values Typ.	Values Max.	Unit
Peak Wavelength	λ_P	I_F=20mA	535	545	555	nm
Half Width	$\Delta\lambda$	I_F=20mA		36		nm
Dominant Wavelength	λ_D	I_F=20mA				
Forward Voltage	V_F	I_F=20mA		3.2		V
Radiated Power *1	P_O	I_F=20mA		2		mW
Radiant Intensity *2	I_E	I_F=20mA		9.3		mW/sr
Brigthness	I_V	I_F=20mA		7		cd
Viewing Angle	φ	I_F=20mA		16		deg.

*1 *measured by S3584-08*
*2 *measured by Tektronix J-6512*

ROITHNER LASERTECHNIK GmbH
WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
TEL. +43 1 586 52 43 -0, FAX. -44 OFFICE@ROITHNER-LASER.COM

Typical Performance Curves

Forward Current vs. Forward Voltage



Rel. Radiant Intensity vs. Forward Current



Forward Current vs. Pulse Duration



Allowed Forward Current vs. Ambient Temperature



Forward Voltage vs. Ambient Temperature



Rel. Radiant Intensity vs. Ambient Temperature



ROITHNER LASERTECHNIK GmbH
WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
TEL. +43 1 586 52 43 -0, FAX. -44 OFFICE@ROITHNER-LASER.COM

Peak Wavelength vs. Ambient Temperature



Relative Spectral Emission



Radiation Characteristics



Outline Dimensions

LED545-01 — **5 mm**



Lead	Description
Short Pin	LED Cathode
Large Pin	LED Anode

All Dimensions in mm

Precautions

Soldering:

- Do avoid overheating of the LED
- Do avoid electrostatic discharge (ESD)
- Do avoid mechanical stress, shock, and vibration
- Do only use non-corrosive flux
- Do not apply current to the LED until it has cooled down to room temperature after soldering
- Do not solder the LED closer than 3 mm from the base of the lead.

Recommended soldering conditions:

Soldering Conditions



Recommended Soldering Patterns



Unit: mm

Above table specifies the maximum allowed duration and temperature during soldering. It is strongly advised to perform soldering at the shortest time and lowest temperature possible.

Cleaning:

Cleaning with isopropyl alcohol, propanol, or ethyl alcohol is recommended
DO NOT USE acetone, chloroseen, trichloroethylene, or MKS
DO NOT USE ultrasonic cleaners

Static Electricity:

LEDs are sensitive to electrostatic discharge (ESD). Precautions against ESD must be taken when handling or operating these LEDs. Surge voltage or electrostatic discharge can result in complete failure of the device.

Radiation:

During operation these LEDs do emit light, which could be hazardous to skin and eyes, and may cause cancer. Do avoid exposure to the emitted light. Protective glasses if needed. It is further advised to attach a warning label on products/systems.

Operation:

Do *only* operate LEDs with a current source.
Running these LEDs from a voltage source will result in complete failure of the device.
Current of a LED is an exponential function of the voltage across it. Usage of current regulated drive circuits is mandatory.

© All Rights Reserved
The above specifications are for reference purpose only and subjected to change without prior notice