

SPECIFICATION SHEET

JFW MODEL 50FHAO-XXX-200

FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-3000 MHz

Impedance 50 Ohms nominal

Attenuation Values 1 thru 50 dB in any 1 dB increment

VSWR For 1-14 dB: 1.4:1 maximum
For 15-50 dB: 1.3:1 maximum

Attenuation Accuracy ± 0.5 dB

RF Input Power 200 Watts average @ +25°C
Derate to 100 Watts @ +85°C

Peak Power 1000 Watts (1 microsecond pulse)

RF Connector SMA, TNC, BNC, N, 4.1-9.5, 4.3-10.0 or 7/16

Operating Temperature Range -55°C to +100°C

Physical Size See outline drawing 092-3728

Optional mounting bracket Part number 004-198
Outline drawing 092-5819

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
16038	06/20/2008	F	SMR 06/20/2008	20523	08/31/2011	I	TRS 08/31/2011
17555	08/14/2008	G	SMR 08/14/2009	26007	12/14/2015	J	CLK 12/14/2015
20288	07/01/2011	H	TRS 07/01/2011	27003	08/29/2016	K	CLK 08/29/2016