Gabellichtschranke
Slotted Interrupter

SFH 9500



Wesentliche Merkmale

- Geeignet für Oberflächenmontage (SMT)
- Kompaktes Gehäuse aus schwarzem LCP
- GaAs-IR-Sendediode (940 nm)
- Si-Fototransistor mit Tageslichtsperrfilter
- Mit Positionspin
- Geeignet für „pick and place“ Montage
- Hohe Genauigkeit (Schlitzbreite 0,5 mm)
- Große Spaltbreite zwischen Sender und Empfänger (5 mm)
- Hohe Stabilität auf PCB durch große Bauelementabmessung (6,8 mm)

Features

- Suitable for surface mounting (SMT)
- Compact housing out of black LCP
- GaAs infrared emitter (940 nm)
- Silicon phototransistor detector with daylight-cutoff filter
- With positioning pin
- Suitable for pick and place
- High sensing accuracy (slit width: 0.5 mm)
- Wide gap between emitter and detector (5 mm)
- High stability on pcb due to large width of device (6.8 mm)

Anwendungen

- Geschwindigkeitsüberwachung
- Motorsteuerung
- Überwachung des Papiervorschubs in Druckern, Kopier- und Faxgeräten
- Speicherlaufwerke
- Steuerung des Druckkopfes in Druckern
- Münzdetektion
- Optoelektronische Schalter

Applications

- Speed control
- Motor control
- Monitoring of paper feed in printers, copiers, facsimiles
- Disk drives
- Control of print head in printers
- Coin detection
- Optoelectronic switches

Typ Type	Bestellnummer Ordering Code	$I_{CE\ min.}$ [mA] (I_F = 20 mA; V_{CE} = 5 V)
SFH 9500	Q62702-P5066	1

Grenzwerte T_A = 25 °C
Maximum Ratings

Bezeichnung **Parameter**	**Symbol** **Symbol**	**Wert** **Value**	**Einheit** **Unit**
Sender (GaAs-Diode) **Emitter** (GaAs Diode)			
Sperrspannung Reverse voltage	V_R	5	V
Durchlaßstrom Forward current	$I_{F\ (DC)}$	60	mA
Verlustleistung Power dissipation	P_{tot}	100	mW
Wärmewiderstand Thermal resistance	R_{thJA}	280	K/W
Empfänger (Si-Fototransistor) **Detector** (Silicon Phototransistor)			
Kollektor-Emitter-Spannung Collector-emitter voltage	V_{CE}	30	V
Kollektor-Emitter-Spannung, ($t \leq 2$ min) Collector-emitter voltage	V_{CE}	70	
Emitter-Kollektor-Spannung Emitter-collector voltage	V_{EC}	7	
Kollektorstrom Collector current	I_C	50	mA
Verlustleistung Total power dissipation	P_{tot}	150	mW
Wärmewiderstand Thermal resistance	R_{thJA}	280	K/W

Grenzwerte T_A = 25 °C
Maximum Ratings (cont'd)

Bezeichnung **Parameter**	**Symbol** **Symbol**	**Wert** **Value**	**Einheit** **Unit**
Gabellichtschranke **Slotted Interrupter**			
Lagertemperatur Storage temperature range	T_{stg}	– 40 … + 85	°C
Betriebstemperatur Operating temperature range	T_{op}	– 40 … + 85	
Elektrostatische Entladung Electrostatic discharge	ESD	2	kV


Kennwerte T_A = 25 °C
Characteristics

Bezeichnung **Parameter**	**Symbol** **Symbol**	**Wert** **Value**	**Einheit** **Unit**
Sender (GaAs-Diode) **Emitter** (GaAs Diode)			
Wellenlänge der Strahlung Wavelength of peak emission	λ_{peak}	940	nm
Durchlaβspannung Forward voltage I_F = 20 m, t_p = 20 ms	V_F	1.2 (≤ 1.4)	V
Sperrstrom Reverse current V_R = 5 V	I_R	0.01 (≤ 1)	µA
Kapazität Capacitance V_R = 0 V, f = 1 MHz	C_0	16	pF
Empfänger (Si-Fototransistor) **Detector** (Silicon Phototransistor)			
Wellenlänge der max. Fotoempfindlichkeit Wavelength of max. sensitivity	$\lambda_{S\ max}$	920	nm
Spectr. Bereich der Fotoempfindlichkeit Spectral range of sensitivity S = 10% of S_{max}	λ	840 … 1080	nm
Kapazität Capacitance V_{CE} = 0 V, f = 1 MHz, E = 0	C_{CE}	6.5	pF
Dunkelstrom, V_{CE} = 20 V Dark current	I_{CEO}	2 (≤ 50)	nA


Kennwerte T_A = 25 °C (cont'd)
Characteristics

Bezeichnung **Parameter**	**Symbol** **Symbol**	**Wert** **Value**	**Einheit** **Unit**
Gabellichtschranke **Slotted interrupter**			
Kollektor-Emitterstrom Collector-emitter current I_F = 20 mA; V_{CE} = 5 V	I_{CE}	> 1	mA
Kollektor-Emitter-Sättigungsspannung Collector-emitter-saturation voltage I_F = 20 mA; I_C = 0.3 mA	$V_{CE\ sat}$	≤ 0.4	V
Anstiegs- und Abfallzeit Rise and fall time V_{CC} = 5 V, I_C = 1 mA, R_L = 1 kΩ	t_r t_f	13 17	µs µs


Forward Current $I_F = f(V_F)$
Single pulse, t_p = 20 µs




Max. Permissible Forward Current
$I_F = f(T_A)$




Dark Current $I_{CEO} = f(T_A)$
V_{CE} = 20 V, E = 0



Total Power Dissipation for Emitter and Detector $P_{tot} = f(T_A)$




Maßzeichnung
Package Outlines



Maße werden wie folgt angegeben: mm (inch) / Dimensions are specified as follows: mm (inch).

Empfohlenes Lötpaddesign IR-Reflow Löten
Recommended Solder Pad IR REflow Soldering




Maße werden wie folgt angegeben: mm (inch) / Dimensions are specified as follows: mm (inch).

Löthinweise
Soldering Conditions

Bauform Type	Reflowlötung Reflow Soldering		Tauch-, Schwalllötung Dip, Wave Soldering
	Peak Temp. of Soldering Zone	Max. Time in Peak Zone	
SFH 9500	245 °C … 215 °C Preheating 150 °C	10 s … 40 s approx. 1 min.	–

IR-Reflow Lötprofil (nach IPC 9501)
IR Reflow Soldering Profile (acc. to IPC 9501)



Published by OSRAM Opto Semiconductors GmbH & Co. OHG
Wernerwerkstrasse 2, D-93049 Regensburg
www.osram-os.com
© All Rights Reserved.
Attention please!
The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.
Packing
Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.
Components used in life-support devices or systems must be expressly authorized for such purpose! Critical components [1] , may only be used in life-support devices or systems [2] with the express written approval of OSRAM OS.
[1] A critical component is a component usedin a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.
[2] Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health of the user may be endangered.